

Arnco

ReSeal™ Volume Chart

INTRODUCTION :

Arnco's ReSeal™ Volume Chart has been produced as an aid for Arnco's customers. We believe you will find this comprehensive chart both useful and easy to use. Just find the tire size designation for the tire you want to add sealant to in the column labeled "Tire", and look across to find the volume of sealant to use in the shaded column labeled "Ounces". Reading the following sections will help you to more fully utilize the information contained in this chart.

CAUTIONS :

While care has been taken to ensure the accuracy of the volumes in the following chart, Arnco is not responsible for any loss or damage that may result from its use.

Use of ReSeal in some high speed tires may result in vibration problems. The customer should determine the suitability of ReSeal for any given application.

No allowance has been made for variations which will occur among different tire brands for a given tire size and rating.

SPECIAL FEATURES :

- Price column :

This column can be used to write in the pricing for sealing various sizes of tires. Or, alternatively, you can have Arnco do it for you. Just let us know what price level(s) you want to use and we will produce a customized version of this chart with all the prices filled in.

- Section III :

This section contains all tires which lack a rim diameter as part of their designation. This only applies to type VII aircraft tires, bicycle tires, some industrial tires, and one special passenger tire. As section II is organized by rim diameter, it is much easier to locate those tires without a rim diameter in their designation in Section III.

ASSUMPTIONS :

The volumes given in the following chart assume the tires are being sealed with ReSeal™. The use of other sealants may require different volumes.

CHART COLUMN 1 : **Rim Diameter**

A separate column of rim diameter is included in this chart because bicycle tires, and some aircraft tires, do not include a rim diameter in their designations.

CHART COLUMN 2 : **Tire Designation**

One of the first things you may notice is that there seems to be a lot of unnecessary spaces in the tire designations used in this chart. The actual designations used on tires do not contain most of the spaces shown. The reason for these extra spaces is to align identical attributes for each tire vertically so that their precise meanings can be more easily understood.

CHART COLUMN 3 : **Tire Class**

The tires listed in this chart have each been sorted into one of eight classes :
Agricultural (AGR), Aircraft (AIR), Bicycle (CYB), Motorcycle (CYM),
Industrial (IND), Off-The-Road (OTR), Passenger (PAS), and Truck & Bus (T&B).

CHART COLUMN 4 : **Ounces**

The volumes shown in this column have been calculated to provide a uniform thickness of sealant for all the tires in each tire class except for passenger tires which have lower thicknesses for low aspect ratio tires to reduce the likelihood of vibration.

CHART COLUMN 5 : **Price**

This column has been left blank so that you can write in prices if desired.

THE CHART COLUMN HEADINGS :

The five column headings of the chart are labeled : Rim Diameter, Tire Designation, Tire Class, Ounces & Price.

CHART COLUMN EXAMPLE

| 1 | 2 | 3 | 4 | 5 |
|--------------|-------------------|------------|--------|-------|
| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
| 4 | 2.80 - 4 NHS | IND | 4 | |
| 4 | 2.80/2.50 - 4 NHS | IND | 4 | |
| 4 | 3.00 - 4 | IND | 6 | |
| 4 | 4.00 - 4 | IND | 8 | |
| 4 | 4.10 - 4 NHS | IND | 6 | |

LISTS OF ABBREVIATIONS :

Abbreviations Used in Tire Prefixes :

| | |
|----|--|
| AT | All Terrain Tire |
| B | Aircraft Tire Rim Width to Section Width Ratio Designation |
| C | Aircraft Tire Rim Width to Section Width Ratio Designation |
| CT | Inverted Flange Tire |
| E | Energy Efficient Tire |
| H | Aircraft Tire Rim Width to Section Width Ratio Designation |
| LT | Light Truck Tire |
| M | Motorcycle Tire |
| P | Passenger Car Tire |
| S | Flotation Service Tire |
| T | Temporary Service (Spare) Tire |

Abbreviations Used in Tire Suffixes :

| | |
|-----|---|
| DT | OTR Tire for Desert Terrain (Sand) |
| FI | Farm Implement Tires |
| HC | Truck & Bus Tire for use with HC contour rims |
| K | Compactor Tire |
| LT | Light Truck Tire |
| MH | Mobile Home Tire |
| ML | Mining & Logging Tire |
| M/C | 15" Diameter Motorcycle Tire for use with specific rims |
| NHS | Not for Highway Service Tire |
| SL | Service Limited to Agriculture Tire |
| SS | Skid Steer Tire |
| ST | Special Trailer Tire |
| TG | Tractor / Grader Tire |
| TR | Truck & Bus Tire for use with specific rims. |
| VA | Agricultural Tire for use with VA contour rims |

Other abbreviations used in this chart :

| | |
|-----|---------------------|
| AGR | Agricultural Tires |
| AIR | Aircraft Tires |
| CYB | Bicycle Tires |
| CYM | Motorcycle Tires |
| IND | Industrial Tires |
| OTR | Off-The-Road Tires |
| PAS | Passenger Car Tires |
| T&B | Truck & Bus Tires |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|---|-------------------|------------|--------|-------|
| 4 | | | 2.80/2.50 - 4 NHS | IND | 6 | |
| 4 | | | 2.80 - 4 NHS | IND | 6 | |
| 4 | | | 3.00 - 4 | IND | 8 | |
| 4 | | | 4.00 - 4 | IND | 10 | |
| 4 | | | 4.10 - 4 NHS | IND | 8 | |
| 4 | | | 4.10/3.50 - 4 NHS | IND | 8 | |
| 4 | | | 4.80 - 4 NHS | IND | 12 | |
| 4 | | | 5.00 - 4 | AIR | 6 | |
| 4 | | | 8.00 - 4 | AIR | 10 | |
| | | | | | | |
| 5 | | | 3.40/3.00 - 5 NHS | IND | 8 | |
| 5 | | | 3.40 - 5 NHS | IND | 8 | |
| 5 | | | 3.50 - 5 | IND | 10 | |
| 5 | 11 | x | 4.00 - 5 NHS | IND | 10 | |
| 5 | | | 4.10/3.50 - 5 NHS | IND | 10 | |
| 5 | | | 4.10 - 5 NHS | IND | 10 | |
| 5 | | | 5.00 - 5 | AIR | 6 | |
| | | | | | | |
| 6 | | | 4.10 - 6 NHS | IND | 10 | |
| 6 | | | 4.10/3.50 - 6 NHS | IND | 10 | |
| 6 | 13 | x | 5.00 - 6 NHS | IND | 12 | |
| 6 | | | 5.30 - 6 NHS | IND | 16 | |
| 6 | | | 5.30/4.50 - 6 NHS | IND | 16 | |
| 6 | 14.5 | x | 5.5 - 6 | AIR | 6 | |
| 6 | | | 6.00 - 6 | AIR | 8 | |
| 6 | 15 | x | 6.0 - 6 | AIR | 8 | |
| 6 | 15 | x | 6.00 - 6 NHS | IND | 18 | |
| 6 | 17.5 | x | 6.25 - 6 | AIR | 8 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price | | |
|--------------|------------------|---|-----------|------------|---------|---------|-----|----|
| 6 | 13 | x | 6.50 | - 6 NHS | IND | 16 | | |
| 6 | | | 6.90/6.00 | - 6 NHS | IND | 24 | | |
| 6 | | | 6.90 | - 6 NHS | IND | 24 | | |
| 6 | | | 7.00 | - 6 | AIR | 10 | | |
| 6 | | | 18 | x | 7/4.50F | NHS | IND | 24 |
| 6 | 13 | x | 7.70 | - 6 NHS | IND | 12 | | |
| 6 | | | 8.00 | - 6 | AIR | 10 | | |
| 6 | | | 8.00 | - 6 NHS | IND | 28 | | |
| 6 | | | 14 | x | 8 | - 6 NHS | IND | 22 |
| 6 | | | | | 8.50 | - 6 | AIR | 14 |
| 6 | | | 9.00 | - 6 | AIR | 14 | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |
| | | | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|-----------|-----|------------|--------|-------|
| 7 | | 4.80 | - 7 | NHS | IND | 12 |
| 7 | 23.5 x | 8.75 | - 7 | | AIR | 12 |
| 8 | | 4.00 | - 8 | | AGR | 14 |
| 8 | | 4.00 | - 8 | | IND | 16 |
| 8 | 16 x | 4.4 | | | AIR | 6 |
| 8 | 15 x | 4 ½ | - 8 | | IND | 14 |
| 8 | 15 x | 4 ½ | R 8 | | IND | 14 |
| 8 | | 4.80/4.00 | - 8 | | IND | 16 |
| 8 | | 4.80 | - 8 | | IND | 16 |
| 8 | | 4.80/4.00 | - 8 | NHS | IND | 16 |
| 8 | | 4.80 | - 8 | NHS | IND | 16 |
| 8 | | 125 / 75 | - 8 | | IND | 14 |
| 8 | | 125 / 75 | R 8 | | IND | 14 |
| 8 | | 5 | - 8 | | AGR | 16 |
| 8 | | 5.00 | - 8 | | IND | 18 |
| 8 | | 5.00 | R 8 | | IND | 20 |
| 8 | 16 x | 5.50 | - 8 | NHS | IND | 18 |
| 8 | 18 x | 5.5 | | | AIR | 8 |
| 8 | | 5.70 | - 8 | | IND | 20 |
| 8 | | 5.70/5.00 | - 8 | | IND | 20 |
| 8 | | 5.70 | - 8 | NHS | IND | 20 |
| 8 | | 5.70/5.00 | - 8 | NHS | IND | 20 |
| 8 | 17.5 x | 5.75 | - 8 | | AIR | 8 |
| 8 | 18 x | 5.75 | - 8 | | AIR | 8 |
| 8 | | 150 / 75 | - 8 | | IND | 20 |
| 8 | | 150 / 75 | R 8 | | IND | 20 |
| 8 | 16 x | 6.00 | - 8 | | IND | 20 |
| 8 | 16 x | 6.00 | R 8 | | IND | 20 |
| 8 | | 6.50 | - 8 | | AIR | 10 |
| 8 | 16 x | 6.50 | - 8 | NHS | IND | 20 |
| 8 | 16.5 x | 6.5 | - 8 | | IND | 20 |
| 8 | 19.5 x | 6.75 | - 8 | | AIR | 10 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|-----|------------|--------|-------|
| 8 | | 7.00 | - 8 | AIR | 10 | |
| 8 | 18 | x 7 | | IND | 26 | |
| 8 | 18 | x 7 | - 8 | IND | 26 | |
| 8 | 18 | x 7 | R 8 | IND | 26 | |
| 8 | 18 | x 7 | - 8 | NHS | IND | 24 |
| 8 | AT 20 | x 7 | - 8 | IND | 28 | |
| 8 | | 180 / 70 | - 8 | IND | 24 | |
| 8 | | 180 / 70 | R 8 | IND | 24 | |
| 8 | 16 | x 7.50 | - 8 | NHS | IND | 24 |
| 8 | 22 | x 8.0 | - 8 | AIR | 12 | |
| 8 | 18 | x 8.50 | - 8 | NHS | IND | 28 |
| 8 | 18.5 | x 8.5 | - 8 | IND | 30 | |
| 8 | 18 | x 9 | - 8 | NHS | IND | 32 |
| 8 | 18 | x 9.50 | - 8 | NHS | IND | 32 |
| 8 | 18.5 | x 9.5 | - 8 | IND | 32 | |
| 8 | AT 18 | x 10 | - 8 | IND | 36 | |
| 8 | AT 20 | x 10 | - 8 | IND | 40 | |
| 8 | AT 22 | x 10 | - 8 | IND | 44 | |
| 8 | AT 23 | x 10 | - 8 | IND | 46 | |
| 8 | AT 18 | x 11 | - 8 | IND | 38 | |
| 8 | AT 20 | x 11 | - 8 | IND | 42 | |
| 8 | 21 | x 11.00 | - 8 | NHS | IND | 46 |
| 8 | AT 21 | x 11 | - 8 | IND | 44 | |
| 8 | 22 | x 11.00 | - 8 | NHS | IND | 48 |
| 8 | AT 22 | x 11 | - 8 | IND | 46 | |
| 8 | AT 21 | x 12 | - 8 | IND | 50 | |
| | | | | | | |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|---------------|------------|--------|-------|
| 9 | | | 4.00 - 9 | SL | AGR | 16 |
| 9 | | | 4.80 - 9 | NHS | IND | 16 |
| 9 | | | 4.80/4.00 - 9 | NHS | IND | 16 |
| 9 | | | 5.00 - 9 | | IND | 20 |
| 9 | | | 6.00 - 9 | | IND | 26 |
| 9 | | | 6.00 R 9 | | IND | 26 |
| 9 | | | 6.90/6.00 - 9 | | IND | 28 |
| 9 | | | 6.90 - 9 | | IND | 28 |
| 9 | | | 6.90 - 9 | NHS | IND | 28 |
| 9 | | | 6.90/6.00 - 9 | NHS | IND | 28 |
| 9 | AT 20 | x 7 | - 9 | | IND | 28 |
| 9 | AT 22 | x 7 | - 9 | | IND | 30 |
| 9 | | 200 / 75 | - 9 | | IND | 32 |
| 9 | | 200 / 75 | R 9 | | IND | 32 |
| 9 | 21 | x 8 | - 9 | | IND | 32 |
| 9 | 21 | x 8 | - 9 | NHS | IND | 32 |
| 9 | AT 21 | x 8 | - 9 | | IND | 32 |
| 9 | 21 | x 9 | - 9 | NHS | IND | 36 |
| 9 | AT 18 | x 11 | - 9 | | IND | 38 |
| 9 | AT 20 | x 11 | - 9 | | IND | 42 |
| 9 | AT 22 | x 11 | - 9 | | IND | 46 |
| 9 | AT 25 | x 12 | - 9 | | IND | 58 |
| 9 | AT 24 | x 13 | - 9 | | IND | 60 |
| 10 | 18 | x 4.25 | - 10 | | AIR | 6 |
| 10 | 18 | x 4.4 | - 10 | | AIR | 6 |
| 10 | | 6.50 | - 10 | | AIR | 10 |
| 10 | | 6.50 | - 10 | | IND | 32 |
| 10 | | 6.50 | R 10 | | IND | 32 |
| 10 | | 6.50 | - 10 | NHS | IND | 32 |
| 10 | 22 | x 6.50 | - 10 | | AIR | 10 |
| 10 | H 19.5 | x 6.75 | - 10 | | AIR | 10 |
| 10 | 22 | x 6.75 | - 10 | | AIR | 10 |
| 10 | AT 21 | x 7 | - 10 | | IND | 30 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|---------------|------------|--------|-------|
| 10 | 21 | x 7.25 | - 10 | AIR | 10 |
| 10 | | 7.50 | - 10 | IND | 40 |
| 10 | | 7.50/9.00 | - 10 | IND | 40 |
| 10 | | 7.50 | R 10 | IND | 40 |
| 10 | | 7.50 L | - 10 NHS | IND | 40 |
| 10 | | 7.50/9.00 | - 10 NHS | IND | 40 |
| 10 | | 7.50 | - 10 NHS | IND | 40 |
| 10 | | 7.50 | - 10 SL | AGR | 38 |
| 10 | 20 | x 7.50 | - 10 NHS | IND | 28 |
| 10 | 24 | x 7.7 | | AIR | 12 |
| 10 | 22 | x 7.75 | - 10 | AIR | 12 |
| 10 | | x 8.00 | - 10 NHS | IND | 28 |
| 10 | AT 20 | x 8 | - 10 | IND | 32 |
| 10 | 20.5 | x 8.0 | - 10 | IND | 32 |
| 10 | 22 | x 8.0 | - 10 | AIR | 12 |
| 10 | AT 22 | x 8 | - 10 | IND | 34 |
| 10 | 23 | x 8 | - 10 NHS | IND | 36 |
| 10 | AT 25 | x 8 | - 10 | IND | 38 |
| 10 | | 8.50 | - 10 | AIR | 16 |
| 10 | | 225 / 75 | - 10 | IND | 40 |
| 10 | | 225 / 75 R 10 | | IND | 40 |
| 10 | | 9.00 | - 10 NHS | IND | 50 |
| 10 | | 9.00 L | - 10 NHS | IND | 48 |
| 10 | | 9.00 | - 10 SL | AGR | 48 |
| 10 | AT 22 | x 9 | - 10 | IND | 38 |
| 10 | 23 | x 9 | - 10 | IND | 40 |
| 10 | 27 | x 9 | - 10 NHS | IND | 48 |
| 10 | AT 18 | x 10 | - 10 | IND | 36 |
| 10 | AT 20 | x 10 | - 10 | IND | 40 |
| 10 | AT 22 | x 10 | - 10 | IND | 44 |
| 10 | AT 18 | x 11 | - 10 | IND | 38 |
| 10 | AT 20 | x 11 | - 10 | IND | 42 |
| 10 | AT 22 | x 11 | - 10 | IND | 46 |
| 10 | AT 24 | x 11 | - 10 | IND | 50 |
| 10 | 29 | x 11.0 | - 10 | AIR | 22 |
| 10 | AT 25 | x 12 | - 10 | IND | 58 |
| 10 | | 15 L | - 10 NHS | IND | 78 |
| 10 | 27 | x 15 | - 10 NHS | IND | 78 |
| 10.5 | B 24 | x 9.5 | - 10.5 | AIR | 16 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|-----------|------|------------|--------|-------|
| 11 | AT 23 | x 8 | - 11 | IND | 36 | |
| 11 | AT 24 | x 8 | - 11 | IND | 38 | |
| 11 | AT 24 | x 9 | - 11 | IND | 42 | |
| 11 | | 10.00 | - 11 | AIR | 20 | |
| | | | | | | |
| 12 | | 4.00 | - 12 | SL | AGR | 18 |
| 12 | | 4.50 | - 12 | | IND | 22 |
| 12 | | 4.80/4.00 | - 12 | | IND | 20 |
| 12 | | 4.80 | - 12 | | IND | 20 |
| 12 | | 4.80 | - 12 | NHS | IND | 20 |
| 12 | | 4.80/4.00 | - 12 | NHS | IND | 20 |
| 12 | | 5 | - 12 | | AGR | 20 |
| 12 | | 5.30/4.50 | - 12 | | IND | 22 |
| 12 | | 5.30 | - 12 | | IND | 22 |
| 12 | | 5.30/4.50 | - 12 | NHS | IND | 22 |
| 12 | | 5.30 | - 12 | NHS | IND | 22 |
| 12 | | 5.70 | - 12 | NHS | IND | 26 |
| 12 | P | 145 / 80 | - 12 | | PAS | 8 |
| 12 | P | 145 / 80 | R 12 | | PAS | 8 |
| 12 | 22 | x 5.75 | - 12 | | AIR | 8 |
| 12 | | 6 | - 12 | | AGR | 26 |
| 12 | P | 155 / 80 | - 12 | | PAS | 10 |
| 12 | P | 155 / 80 | R 12 | | PAS | 10 |
| 12 | P | 165 / 70 | - 12 | | PAS | 10 |
| 12 | P | 165 / 70 | R 12 | | PAS | 10 |
| 12 | | 7.00 | - 12 | NHS | IND | 40 |
| 12 | | 7.00 | R 12 | NHS | IND | 38 |
| 12 | 23 | x 7.0 | - 12 | | AIR | 12 |
| 12 | 24 | x 7.25 | - 12 | | AIR | 12 |
| 12 | 22 | x 7.50 | - 12 | NHS | IND | 34 |
| 12 | 22 | x 8.00 | - 12 | NHS | IND | 34 |
| 12 | 23 | x 8 | - 12 | NHS | IND | 36 |
| 12 | | 8.25 | - 12 | | IND | 48 |
| 12 | 23 | x 8.50 | - 12 | | IND | 36 |
| 12 | 23 | x 8.50 | - 12 | NHS | IND | 36 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|------|----------|------------|--------|-------|
| 12 | | 23.5 | x 8.5 | - 12 | IND | 38 |
| 12 | C | 24.5 | x 8.5 | - 12 | AIR | 14 |
| 12 | | 23 | x 9 | - 12 | NHS | 40 |
| 12 | | 28 | x 9.0 | - 12 | AIR | 18 |
| 12 | | 23 | x 9.50 | - 12 | NHS | 44 |
| 12 | | | 250 / 75 | - 12 | IND | 52 |
| 12 | | | 250 / 75 | R 12 | IND | 52 |
| 12 | | 23 | x 10 | - 12 | NHS | 46 |
| 12 | | 27 | x 10 | - 12 | IND | 52 |
| 12 | | 27 | x 10 | - 12 | NHS | 52 |
| 12 | | 23 | x 10.50 | - 12 | NHS | 46 |
| 12 | | | 11.00 | - 12 | AIR | 26 |
| 12 | | 23.5 | x 11 | - 12 | NHS | 50 |
| 12 | | 24 | x 12 | - 12 | NHS | 56 |
| 12 | | 25 | x 12 | - 12 | NHS | 58 |
| 12 | | 26 | x 12.00 | - 12 | NHS | 60 |
| 12 | H | 31 | x 13.0 | - 12 | AIR | 26 |
| 12 | | | 15.00 | - 12 | AIR | 34 |
| 12.31 | | 16 | x 1.75 | | CYB | 4 |
| 12.31 | | 16 | x 2.125 | | CYB | 6 |
| 12.48 | | 16 | x 1 3/4 | | CYB | 4 |
| 12.50 | | | 8.90 | - 12.50 | AIR | 16 |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|---------------|------------|--------|-------|
| 13 | 21 | x 4 | IND | 20 | |
| 13 | T | 105 / 80 - 13 | PAS | 6 | |
| 13 | T | 105 / 80 R 13 | PAS | 6 | |
| 13 | 22 | x 4½ | IND | 26 | |
| 13 | T | 125 / 80 - 13 | PAS | 8 | |
| 13 | T | 125 / 80 R 13 | PAS | 8 | |
| 13 | 23 | x 5 | IND | 30 | |
| 13 | P | 145 / 80 - 13 | PAS | 10 | |
| 13 | P | 145 / 80 R 13 | PAS | 10 | |
| 13 | 25 | x 6 | IND | 34 | |
| 13 | P | 155 / 70 - 13 | PAS | 10 | |
| 13 | P | 155 / 70 R 13 | PAS | 10 | |
| 13 | P | 155 / 80 - 13 | PAS | 10 | |
| 13 | P | 155 / 80 R 13 | PAS | 10 | |
| 13 | P | 165 / 65 R 13 | PAS | 10 | |
| 13 | P | 165 / 70 - 13 | PAS | 10 | |
| 13 | P | 165 / 70 R 13 | PAS | 10 | |
| 13 | P | 165 / 75 - 13 | PAS | 10 | |
| 13 | P | 165 / 75 R 13 | PAS | 10 | |
| 13 | P | 165 / 80 - 13 | PAS | 10 | |
| 13 | P | 165 / 80 R 13 | PAS | 10 | |
| 13 | | 6.50 - 13 | ST | T&B | 12 |
| 13 | | A 78 - 13 | PAS | 10 | |
| 13 | | A 78 - 13 | ST | T&B | 10 |
| 13 | | B R 78 - 13 | PAS | 12 | |
| 13 | P | 175 / 70 - 13 | PAS | 10 | |
| 13 | P | 175 / 70 R 13 | PAS | 10 | |
| 13 | LT | 175 / 75 - 13 | T&B | 12 | |
| 13 | LT | 175 / 75 R 13 | T&B | 12 | |
| 13 | P | 175 / 75 - 13 | PAS | 12 | |
| 13 | P | 175 / 75 R 13 | PAS | 12 | |
| 13 | P | 175 / 80 - 13 | PAS | 12 | |
| 13 | P | 175 / 80 R 13 | PAS | 12 | |
| 13 | ST | 175 / 80 R 13 | T&B | 12 | |
| 13 | | B 78 - 13 | PAS | 12 | |
| 13 | | B 78 - 13 | ST | T&B | 12 |
| 13 | | A 70 - 13 | PAS | 12 | |
| 13 | | C 78 - 13 | PAS | 12 | |
| 13 | | C 78 - 13 | ST | T&B | 12 |
| 13 | P | 185 / 60 - 13 | PAS | 10 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|-------------------|------------|--------|-------|
| 13 | P 185 / 60 R 13 | PAS | 10 | |
| 13 | P 185 / 70 - 13 | PAS | 12 | |
| 13 | P 185 / 70 R 13 | PAS | 12 | |
| 13 | P 185 / 75 - 13 | PAS | 12 | |
| 13 | P 185 / 75 R 13 | PAS | 12 | |
| 13 | P 185 / 80 - 13 | PAS | 12 | |
| 13 | P 185 / 80 R 13 | PAS | 12 | |
| 13 | ST 185 / 80 R 13 | T&B | 12 | |
| 13 | B 70 - 13 | PAS | 12 | |
| 13 | 24 x 7.50 - 13 LT | T&B | 12 | |
| 13 | 24 x 7.50 R 13 LT | T&B | 12 | |
| 13 | B R 70 - 13 | PAS | 12 | |
| 13 | P 195 / 60 - 13 | PAS | 12 | |
| 13 | P 195 / 60 R 13 | PAS | 12 | |
| 13 | P 195 / 65 R 13 | PAS | 12 | |
| 13 | P 195 / 70 - 13 | PAS | 12 | |
| 13 | P 195 / 70 R 13 | PAS | 12 | |
| 13 | D 78 - 13 | PAS | 12 | |
| 13 | A 60 - 13 | PAS | 12 | |
| 13 | P 205 / 60 - 13 | PAS | 12 | |
| 13 | P 205 / 60 R 13 | PAS | 12 | |
| 13 | P 205 / 70 - 13 | PAS | 14 | |
| 13 | P 205 / 70 R 13 | PAS | 14 | |
| 13 | B 60 - 13 | PAS | 14 | |
| 13 | B R 60 - 13 | PAS | 14 | |
| 13 | P 215 / 50 - 13 | PAS | 12 | |
| 13 | P 215 / 50 R 13 | PAS | 12 | |
| 13 | P 215 / 60 - 13 | PAS | 14 | |
| 13 | P 215 / 60 R 13 | PAS | 14 | |
| 13 | P 225 / 75 - 13 | PAS | 14 | |
| 13 | P 225 / 75 R 13 | PAS | 14 | |
| 13 | B 50 - 13 | PAS | 14 | |
| 13 | P 235 / 50 - 13 | PAS | 14 | |
| 13 | P 235 / 50 R 13 | PAS | 14 | |
| 13 | P 235 / 60 - 13 | PAS | 14 | |
| 13 | P 235 / 60 R 13 | PAS | 14 | |
| 13 | P 245 / 50 - 13 | PAS | 14 | |
| 13 | P 245 / 50 R 13 | PAS | 14 | |
| 13 | H 31 x 9.75 - 13 | AIR | 20 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|-------------------|------------|--------|-------|
| 14 | M 90 / 100 - 14 | CYM | 6 | |
| 14 | T 105 / 70 - 14 | PAS | 6 | |
| 14 | T 105 / 70 R 14 | PAS | 6 | |
| 14 | T 115 / 70 - 14 | PAS | 8 | |
| 14 | T 115 / 70 R 14 | PAS | 8 | |
| 14 | T 125 / 70 - 14 | PAS | 8 | |
| 14 | T 125 / 70 R 14 | PAS | 8 | |
| 14 | T 135 / 70 - 14 | PAS | 8 | |
| 14 | T 135 / 70 R 14 | PAS | 8 | |
| 14 | T 135 / 80 - 14 | PAS | 8 | |
| 14 | T 135 / 80 R 14 | PAS | 8 | |
| 14 | 6.00 - 14 SL | AGR | 34 | |
| 14 | E 165 / 65 R 14 | PAS | 10 | |
| 14 | P 165 / 80 - 14 | PAS | 10 | |
| 14 | P 165 / 80 R 14 | PAS | 10 | |
| 14 | 26 x 6.6 | AIR | 12 | |
| 14 | B 78 - 14 | PAS | 12 | |
| 14 | 25.75 x 6.75 - 14 | AIR | 12 | |
| 14 | 26 x 6.75 - 14 | AIR | 12 | |
| 14 | P 175 / 60 - 14 | PAS | 10 | |
| 14 | P 175 / 60 R 14 | PAS | 10 | |
| 14 | E 175 / 65 R 14 | PAS | 12 | |
| 14 | P 175 / 65 R 14 | PAS | 12 | |
| 14 | P 175 / 70 - 14 | PAS | 12 | |
| 14 | P 175 / 70 R 14 | PAS | 12 | |
| 14 | LT 175 / 75 - 14 | T&B | 12 | |
| 14 | LT 175 / 75 R 14 | T&B | 12 | |
| 14 | P 175 / 75 - 14 | PAS | 12 | |
| 14 | P 175 / 75 R 14 | PAS | 12 | |
| 14 | P 175 / 80 - 14 | PAS | 12 | |
| 14 | P 175 / 80 R 14 | PAS | 12 | |
| 14 | 7.00 - 14 LT | T&B | 14 | |
| 14 | 7.00 R 14 LT | T&B | 14 | |
| 14 | C 78 - 14 | PAS | 12 | |
| 14 | D R 78 - 14 | PAS | 12 | |
| 14 | P 185 / 60 - 14 | PAS | 12 | |
| 14 | P 185 / 60 R 14 | PAS | 12 | |
| 14 | P 185 / 65 R 14 | PAS | 12 | |
| 14 | P 185 / 70 - 14 | PAS | 12 | |
| 14 | P 185 / 70 R 14 | PAS | 12 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|------------------|--------|------|------|------------|--------|-------|
| 14 | | F | 70 | - 14 | ST | T&B | 14 |
| 14 | | G R | 78 | - 14 | | PAS | 14 |
| 14 | | G | 78 | - 14 | | PAS | 16 |
| 14 | | G | 78 | - 14 | LT | T&B | 16 |
| 14 | | G | 78 | - 14 | ST | T&B | 16 |
| 14 | P | 215 / | 60 | - 14 | | PAS | 14 |
| 14 | P | 215 / | 60 R | 14 | | PAS | 14 |
| 14 | P | 215 / | 65 R | 14 | | PAS | 14 |
| 14 | P | 215 / | 70 | - 14 | | PAS | 14 |
| 14 | P | 215 / | 70 R | 14 | | PAS | 14 |
| 14 | LT | 215 / | 75 | - 14 | | T&B | 16 |
| 14 | LT | 215 / | 75 R | 14 | | T&B | 16 |
| 14 | P | 215 / | 75 | - 14 | | PAS | 16 |
| 14 | P | 215 / | 75 R | 14 | | PAS | 16 |
| 14 | ST | 215 / | 75 R | 14 | | T&B | 16 |
| 14 | | 8.5 | | R 14 | LT | T&B | 14 |
| 14 | | 8.5 | L | - 14 | SL | AGR | 46 |
| 14 | 26 | x 8.50 | | - 14 | LT | T&B | 14 |
| 14 | 26 | x 8.50 | | R 14 | LT | T&B | 14 |
| 14 | 27 | x 8.50 | | - 14 | LT | T&B | 16 |
| 14 | 27 | x 8.50 | | R 14 | LT | T&B | 16 |
| 14 | | F R | 70 | - 14 | | PAS | 16 |
| 14 | | H | 78 | - 14 | | PAS | 16 |
| 14 | | H | 78 | - 14 | ST | T&B | 16 |
| 14 | | G | 70 | - 14 | | PAS | 16 |
| 14 | | G R | 70 | - 14 | | PAS | 16 |
| 14 | P | 225 / | 60 | - 14 | | PAS | 14 |
| 14 | P | 225 / | 60 R | 14 | | PAS | 14 |
| 14 | P | 225 / | 70 | - 14 | | PAS | 16 |
| 14 | P | 225 / | 70 R | 14 | | PAS | 16 |
| 14 | P | 225 / | 75 | - 14 | | PAS | 16 |
| 14 | P | 225 / | 75 R | 14 | | PAS | 16 |
| 14 | | 9 | | - 14 | LT | T&B | 18 |
| 14 | | E | 60 | - 14 | | PAS | 16 |
| 14 | | E R | 60 | - 14 | | PAS | 16 |
| 14 | | H | 70 | - 14 | | PAS | 16 |
| 14 | | H | 70 | - 14 | ST | T&B | 16 |
| 14 | P | 235 / | 60 | - 14 | | PAS | 16 |
| 14 | P | 235 / | 60 R | 14 | | PAS | 16 |
| 14 | P | 235 / | 70 | - 14 | | PAS | 16 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|----|------------------|-------|--------|------|------------|--------|-------|
| 14 | P | 235 | / | 70 | R 14 | PAS | 16 | |
| 14 | | F | R | 60 | - 14 | PAS | 16 | |
| 14 | | 9.5 | L | | - 14 | SL | 56 | |
| 14 | 27 | x | 9.50 | | - 14 | LT | 16 | |
| 14 | 27 | x | 9.50 | | R 14 | LT | 16 | |
| 14 | 29 | x | 9.50 | | - 14 | LT | 18 | |
| 14 | 29 | x | 9.50 | | R 14 | LT | 18 | |
| 14 | | F | | 60 | - 14 | PAS | 16 | |
| 14 | P | 245 | / | 50 | - 14 | PAS | 16 | |
| 14 | P | 245 | / | 50 | R 14 | PAS | 16 | |
| 14 | P | 245 | / | 60 | - 14 | PAS | 16 | |
| 14 | P | 245 | / | 60 | R 14 | PAS | 16 | |
| 14 | P | 245 | / | 70 | - 14 | PAS | 18 | |
| 14 | P | 245 | / | 70 | R 14 | PAS | 18 | |
| 14 | | G | R | 60 | - 14 | PAS | 16 | |
| 14 | | G | | 60 | - 14 | PAS | 16 | |
| 14 | P | 255 | / | 55 | R 14 | PAS | 16 | |
| 14 | P | 255 | / | 60 | - 14 | PAS | 18 | |
| 14 | P | 255 | / | 60 | R 14 | PAS | 18 | |
| 14 | P | 265 | / | 50 | - 14 | PAS | 18 | |
| 14 | P | 265 | / | 50 | R 14 | PAS | 18 | |
| 14 | P | 265 | / | 60 | - 14 | PAS | 18 | |
| 14 | P | 265 | / | 60 | R 14 | PAS | 18 | |
| 14 | P | 275 | / | 60 | - 14 | PAS | 20 | |
| 14 | P | 275 | / | 60 | R 14 | PAS | 20 | |
| 14 | | G | | 50 | - 14 | PAS | 18 | |
| 14 | | 11 | | | - 14 | LT | 22 | |
| 14 | | 11 | L | | - 14 | SL | 62 | |
| 14 | 34 | x | 11 | | | AIR | 24 | |
| 14 | | L | | 60 | - 14 | PAS | 20 | |
| 14 | | M | | 50 | - 14 | PAS | 22 | |
| 14 | 37 | x | 14.0 | | - 14 | AIR | 34 | |
| 14.31 | 18 | x | 1.625 | | | CYB | 4 | |
| 14.5 | | 7 | | - 14.5 | LT | T&B | 14 | |
| 14.5 | | 7 | | - 14.5 | MH | T&B | 14 | |
| 14.5 | | 8 | | - 14.5 | LT | T&B | 14 | |
| 14.5 | | 8 | | - 14.5 | MH | T&B | 14 | |
| 14.5 | | 9 | | - 14.5 | LT | T&B | 18 | |
| 14.5 | | 9 | | - 14.5 | MH | T&B | 18 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | Tire Class | Ounces | Price |
|--------------|---|------------------|---------|------------|--------|-------|
| 15 | | 4.00 | - 15 | SL | AGR | 22 |
| 15 | T | 105 / 70 | - 15 | | PAS | 6 |
| 15 | T | 105 / 70 | R 15 | | PAS | 6 |
| 15 | T | 115 / 70 | - 15 | | PAS | 8 |
| 15 | T | 115 / 70 | R 15 | | PAS | 8 |
| 15 | T | 125 / 70 | - 15 | | PAS | 8 |
| 15 | T | 125 / 70 | R 15 | | PAS | 8 |
| 15 | T | 125 / 90 | - 15 | | PAS | 8 |
| 15 | T | 125 / 90 | R 15 | | PAS | 8 |
| 15 | | 5.00 | - 15 | SL | AGR | 26 |
| 15 | T | 135 / 70 | - 15 | | PAS | 8 |
| 15 | T | 135 / 70 | R 15 | | PAS | 8 |
| 15 | T | 135 / 80 | - 15 | | PAS | 10 |
| 15 | T | 135 / 80 | R 15 | | PAS | 10 |
| 15 | T | 135 / 90 | - 15 | | PAS | 10 |
| 15 | T | 135 / 90 | R 15 | | PAS | 10 |
| 15 | | 5.50 | - 15 | | IND | 32 |
| 15 | M | 140 / 80 | - 15 | M/C | CYM | 10 |
| 15 | M | 140 / 90 | - 15 | M/C | CYM | 10 |
| 15 | M | 140 / 90 | R 15 | M/C | CYM | 10 |
| 15 | M | U | 90 - 15 | M/C | CYM | 10 |
| 15 | | 5.70 | - 15 | NHS | IND | 28 |
| 15 | | 5.90 | - 15 | SL | AGR | 32 |
| 15 | M | V | 85 - 15 | M/C | CYM | 10 |
| 15 | M | V | 90 - 15 | M/C | CYM | 12 |
| 15 | M | 150 / 90 | R 15 | M/C | CYM | 12 |
| 15 | | 6.00 | - 15 | | IND | 34 |
| 15 | | 6.10 | - 15 | LT | T&B | 10 |
| 15 | | 6.10 | R 15 | LT | T&B | 10 |
| 15 | P | 155 / 80 | - 15 | | PAS | 10 |
| 15 | P | 155 / 80 | R 15 | | PAS | 10 |
| 15 | | A | 78 - 15 | | PAS | 10 |
| 15 | | 6.40 | - 15 | SL | AGR | 34 |
| 15 | P | 165 / 80 | - 15 | | PAS | 12 |
| 15 | P | 165 / 80 | R 15 | | PAS | 12 |
| 15 | M | 170 / 70 | - 15 | M/C | CYM | 12 |
| 15 | M | 170 / 80 | - 15 | M/C | CYM | 12 |
| 15 | M | 170 / 80 | R 15 | M/C | CYM | 12 |
| 15 | | 6.70 | - 15 | LT | T&B | 14 |
| 15 | | 6.70 | R 15 | LT | T&B | 14 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|---------|------------|--------|-------|
| 15 | | 6.70 | - 15 | SL | AGR | 36 |
| 15 | | 7.00 | - 15 | | IND | 44 |
| 15 | | 7.00 | R 15 | | IND | 44 |
| 15 | | 7.00 | - 15 | LT | T&B | 16 |
| 15 | | 7.00 | R 15 | LT | T&B | 16 |
| 15 | | 7.00 | L - 15 | NHS | IND | 44 |
| 15 | | 7.00 | - 15 | NHS | IND | 46 |
| 15 | | 7.00 | - 15 | SS | IND | 46 |
| 15 | | 7.00 | - 15 | TR | T&B | 16 |
| 15 | | 7.00 | R 15 | TR | T&B | 16 |
| 15 | | 7.10 | - 15 | LT | T&B | 16 |
| 15 | | 7.10 | R 15 | LT | T&B | 16 |
| 15 | P | 185 / 60 | - 15 | | PAS | 12 |
| 15 | P | 185 / 60 | R 15 | | PAS | 12 |
| 15 | P | 185 / 65 | R 15 | | PAS | 12 |
| 15 | P | 185 / 70 | - 15 | | PAS | 12 |
| 15 | P | 185 / 70 | R 15 | | PAS | 12 |
| 15 | | E 78 | - 15 | | PAS | 14 |
| 15 | | E 78 | - 15 | ST | T&B | 14 |
| 15 | | 7.50 | - 15 | | IND | 50 |
| 15 | | 7.50 | R 15 | | IND | 48 |
| 15 | | 7.50 | - 15 | LT | T&B | 18 |
| 15 | | 7.50 | R 15 | LT | T&B | 18 |
| 15 | | 7.50 | - 15 30 | NHS | IND | 46 |
| 15 | | 7.50 | - 15 | NHS | OTR | 52 |
| 15 | | 7.50 | - 15 | NHS | IND | 52 |
| 15 | | 7.5 | L - 15 | SL | AGR | 46 |
| 15 | | 7.50 | - 15 | TR | T&B | 18 |
| 15 | | 7.50 | R 15 | TR | T&B | 18 |
| 15 | 25 x | 7.50 | - 15 | NHS | A&I | 38 |
| 15 | | 7.60 | - 15 | SL | AGR | 44 |
| 15 | P | 195 / 50 | - 15 | | PAS | 12 |
| 15 | P | 195 / 50 | R 15 | | PAS | 12 |
| 15 | P | 195 / 60 | - 15 | | PAS | 12 |
| 15 | P | 195 / 60 | R 15 | | PAS | 12 |
| 15 | P | 195 / 65 | R 15 | | PAS | 14 |
| 15 | P | 195 / 70 | - 15 | | PAS | 14 |
| 15 | P | 195 / 70 | R 15 | | PAS | 14 |
| 15 | LT | 195 / 75 | - 15 | | T&B | 14 |
| 15 | LT | 195 / 75 | R 15 | | T&B | 14 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|------------------|---|----------|------|------------|--------|-------|
| 15 | P | | 195 / 75 | - 15 | PAS | 14 | |
| 15 | P | | 195 / 75 | R 15 | PAS | 14 | |
| 15 | P | | 195 / 80 | - 15 | PAS | 14 | |
| 15 | P | | 195 / 80 | R 15 | PAS | 14 | |
| 15 | | | F R 78 | - 15 | PAS | 14 | |
| 15 | | | F 78 | - 15 | PAS | 14 | |
| 15 | 29 | x | 7.7 | | AIR | 14 | |
| 15 | | | 7.75 | - 15 | ST | 14 | |
| 15 | | | F 78 | - 15 | ST | 14 | |
| 15 | 27 | x | 7.75 | - 15 | AIR | 14 | |
| 15 | 28 | x | 8 | - 15 | IND | 44 | |
| 15 | 29 | x | 8 | - 15 | NHS | 44 | |
| 15 | 30 | x | 8 | - 15 | NHS | 46 | |
| 15 | | | G 78 | - 15 | PAS | 14 | |
| 15 | | | G 78 | - 15 | ST | 14 | |
| 15 | P | | 205 / 50 | - 15 | PAS | 12 | |
| 15 | P | | 205 / 50 | R 15 | PAS | 12 | |
| 15 | P | | 205 / 55 | R 15 | PAS | 12 | |
| 15 | P | | 205 / 60 | - 15 | PAS | 14 | |
| 15 | P | | 205 / 60 | R 15 | PAS | 14 | |
| 15 | P | | 205 / 65 | R 15 | PAS | 14 | |
| 15 | | | 205 / 70 | R 15 | IND | 42 | |
| 15 | P | | 205 / 70 | - 15 | PAS | 14 | |
| 15 | P | | 205 / 70 | R 15 | PAS | 14 | |
| 15 | LT | | 205 / 75 | - 15 | T&B | 14 | |
| 15 | LT | | 205 / 75 | R 15 | T&B | 14 | |
| 15 | P | | 205 / 75 | - 15 | PAS | 14 | |
| 15 | P | | 205 / 75 | R 15 | PAS | 14 | |
| 15 | ST | | 205 / 75 | R 15 | T&B | 14 | |
| 15 | | | 8.15 | - 15 | IND | 46 | |
| 15 | | | 8.15 | - 15 | NHS | 48 | |
| 15 | | | G R 78 | - 15 | PAS | 16 | |
| 15 | | | 8.25 | - 15 | IND | 60 | |
| 15 | | | 8.25 | R 15 | IND | 58 | |
| 15 | | | 8.25 | - 15 | NHS | 60 | |
| 15 | | | 8.25 | - 15 | SS | 58 | |
| 15 | | | 8.25 | - 15 | TR | 20 | |
| 15 | | | 8.25 | R 15 | TR | 20 | |
| 15 | | | F 70 | - 15 | PAS | 16 | |
| 15 | | | G 78 | - 15 | LT | 16 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|------------------|---|-------|---------|------------|--------|-------|
| 15 | | | G R | 78 - 15 | LT | T&B | 16 |
| 15 | | | H R | 78 - 15 | | PAS | 16 |
| 15 | P | | 215 / | 60 - 15 | | PAS | 14 |
| 15 | P | | 215 / | 60 R 15 | | PAS | 14 |
| 15 | P | | 215 / | 65 R 15 | | PAS | 14 |
| 15 | P | | 215 / | 70 - 15 | | PAS | 16 |
| 15 | P | | 215 / | 70 R 15 | | PAS | 16 |
| 15 | LT | | 215 / | 75 - 15 | | T&B | 16 |
| 15 | LT | | 215 / | 75 R 15 | | T&B | 16 |
| 15 | P | | 215 / | 75 - 15 | | PAS | 16 |
| 15 | P | | 215 / | 75 R 15 | | PAS | 16 |
| 15 | | | 8.5 / | 90 - 15 | K | OTR | 52 |
| 15 | 27 | x | 8.50 | - 15 | NHS | AGR | 44 |
| 15 | 27 | x | 8.50 | - 15 | NHS | IND | 44 |
| 15 | 28 | x | 8.50 | - 15 | LT | T&B | 16 |
| 15 | 28 | x | 8.50 | R 15 | LT | T&B | 16 |
| 15 | | | 8.55 | - 15 | ST | T&B | 16 |
| 15 | | | H | 78 - 15 | | PAS | 16 |
| 15 | | | H | 78 - 15 | ST | T&B | 16 |
| 15 | | | G | 70 - 15 | | PAS | 16 |
| 15 | | | J R | 78 - 15 | | PAS | 16 |
| 15 | | | G R | 70 - 15 | | PAS | 16 |
| 15 | | | J | 78 - 15 | | PAS | 16 |
| 15 | | | H | 78 - 15 | LT | T&B | 16 |
| 15 | | | H R | 78 - 15 | LT | T&B | 16 |
| 15 | 30 | x | 8.8 | R 15 | | AIR | 20 |
| 15 | | | L | 78 - 15 | | PAS | 18 |
| 15 | P | | 225 / | 50 - 15 | | PAS | 14 |
| 15 | P | | 225 / | 50 R 15 | | PAS | 14 |
| 15 | P | | 225 / | 55 R 15 | | PAS | 14 |
| 15 | P | | 225 / | 60 - 15 | | PAS | 16 |
| 15 | P | | 225 / | 60 R 15 | | PAS | 16 |
| 15 | P | | 225 / | 65 R 15 | | PAS | 16 |
| 15 | P | | 225 / | 70 - 15 | | PAS | 16 |
| 15 | P | | 225 / | 70 R 15 | | PAS | 16 |
| 15 | P | | 225 / | 75 R 15 | | IND | 50 |
| 15 | P | | 225 / | 75 - 15 | | PAS | 16 |
| 15 | P | | 225 / | 75 R 15 | | PAS | 16 |
| 15 | ST | | 225 / | 75 R 15 | | T&B | 16 |
| 15 | | | H | 70 - 15 | | PAS | 16 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------|------------|--------|-------|
| 15 | | 9.00 | - 15 | DT | OTR | 60 |
| 15 | | 9.00 | R 15 | DT | OTR | 60 |
| 15 | | 9 | - 15 | LT | T&B | 20 |
| 15 | | 9 | R 15 | LT | T&B | 20 |
| 15 | | 9.00 | - 15 | NHS | IND | 72 |
| 15 | | 9.00 | - 15 | TR | T&B | 24 |
| 15 | | 9.00 | R 15 | TR | T&B | 24 |
| 15 | | L R 78 | - 15 | | PAS | 18 |
| 15 | 28 | x 9 | - 15 | | IND | 46 |
| 15 | 28 | x 9 | - 15 | NHS | IND | 46 |
| 15 | | F 60 | - 15 | | PAS | 16 |
| 15 | | H R 70 | - 15 | | PAS | 18 |
| 15 | P | 235 / 60 | - 15 | | PAS | 16 |
| 15 | P | 235 / 60 | R 15 | | PAS | 16 |
| 15 | P | 235 / 65 | R 15 | | PAS | 16 |
| 15 | P | 235 / 70 | - 15 | | PAS | 18 |
| 15 | P | 235 / 70 | R 15 | | PAS | 18 |
| 15 | LT | 235 / 75 | - 15 | | T&B | 18 |
| 15 | LT | 235 / 75 | R 15 | | T&B | 18 |
| 15 | P | 235 / 75 | - 15 | | PAS | 18 |
| 15 | P | 235 / 75 | R 15 | | PAS | 18 |
| 15 | | L R 78 | - 15 | LT | T&B | 18 |
| 15 | | L 78 | - 15 | LT | T&B | 18 |
| 15 | | K 70 | - 15 | | PAS | 18 |
| 15 | | 9.50 | - 15 | FI | AGR | 46 |
| 15 | | 9.5 L | - 15 | FI | AGR | 58 |
| 15 | | 9.5 L | - 15 | SL | AGR | 58 |
| 15 | | G R 60 | - 15 | | PAS | 16 |
| 15 | 27 | x 9.50 | - 15 | LT | T&B | 16 |
| 15 | 27 | x 9.50 | R 15 | LT | T&B | 16 |
| 15 | 27 | x 9.50 | - 15 | NHS | A&I | 46 |
| 15 | 29 | x 9.50 | - 15 | LT | T&B | 18 |
| 15 | 29 | x 9.50 | R 15 | LT | T&B | 18 |
| 15 | 30 | x 9.50 | - 15 | LT | T&B | 18 |
| 15 | 30 | x 9.50 | R 15 | LT | T&B | 18 |
| 15 | | 9.60 | - 15 | SL | AGR | 20 |
| 15 | | L 70 | - 15 | | PAS | 18 |
| 15 | P | 245 / 50 | - 15 | | PAS | 16 |
| 15 | P | 245 / 50 | R 15 | | PAS | 16 |
| 15 | P | 245 / 60 | - 15 | | PAS | 18 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------|------------|--------|-------|
| 15 | P | 245 / 60 | R 15 | PAS | 18 | |
| 15 | P | 245 / 65 | R 15 | PAS | 18 | |
| 15 | P | 245 / 70 | - 15 | PAS | 18 | |
| 15 | P | 245 / 70 | R 15 | PAS | 18 | |
| 15 | | L R 70 | - 15 | PAS | 18 | |
| 15 | | G 60 | - 15 | PAS | 18 | |
| 15 | | N 78 | - 15 | PAS | 20 | |
| 15 | | 250 | - 15 | IND | 54 | |
| 15 | | 250 | - 15 | NHS IND | 56 | |
| 15 | | 250 / 70 | - 15 | IND | 56 | |
| 15 | | 250 / 70 | R 15 | IND | 56 | |
| 15 | | 10.00 | - 15 | IND | 74 | |
| 15 | | 10.00 | R 15 | IND | 74 | |
| 15 | | 10 | - 15 | LT T&B | 20 | |
| 15 | | 10 | R 15 | LT T&B | 20 | |
| 15 | | 10.00 L | - 15 | NHS IND | 76 | |
| 15 | | 10.00 | - 15 | NHS IND | 80 | |
| 15 | | 10.00 | - 15 | SL AGR | 70 | |
| 15 | | 10.00 | - 15 | TR T&B | 26 | |
| 15 | | 10.00 | R 15 | TR T&B | 26 | |
| 15 | 29 x 10 | | - 15 | NHS IND | 56 | |
| 15 | P | 255 / 55 | R 15 | PAS | 18 | |
| 15 | P | 255 / 60 | - 15 | PAS | 18 | |
| 15 | P | 255 / 60 | R 15 | PAS | 18 | |
| 15 | P | 255 / 65 | R 15 | PAS | 18 | |
| 15 | P | 255 / 70 | - 15 | PAS | 20 | |
| 15 | P | 255 / 70 | R 15 | PAS | 20 | |
| 15 | LT | 255 / 75 | - 15 | T&B | 20 | |
| 15 | LT | 255 / 75 | R 15 | T&B | 20 | |
| 15 | | H R 60 | - 15 | PAS | 18 | |
| 15 | | H 60 | - 15 | PAS | 18 | |
| 15 | | G 50 | - 15 | PAS | 18 | |
| 15 | P | 265 / 50 | - 15 | PAS | 18 | |
| 15 | P | 265 / 50 | R 15 | PAS | 18 | |
| 15 | P | 265 / 60 | - 15 | PAS | 20 | |
| 15 | P | 265 / 60 | R 15 | PAS | 20 | |
| 15 | P | 265 / 75 | - 15 | PAS | 22 | |
| 15 | P | 265 / 75 | R 15 | PAS | 22 | |
| 15 | | L 60 | - 15 | PAS | 20 | |
| 15 | | L R 60 | - 15 | PAS | 20 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|------------------|-------|----------|------|------------|--------|-------|
| 15 | 27 | x | 10.50 | - 15 | NHS | A&I | 52 |
| 15 | 31 | x | 10.50 | - 15 | LT | T&B | 22 |
| 15 | 31 | x | 10.50 | R 15 | LT | T&B | 22 |
| 15 | 33 | x | 10.50 | - 15 | LT | T&B | 22 |
| 15 | 33 | x | 10.50 | R 15 | LT | T&B | 22 |
| 15 | P | | 275 / 50 | - 15 | | PAS | 18 |
| 15 | P | | 275 / 50 | R 15 | | PAS | 18 |
| 15 | P | | 275 / 60 | - 15 | | PAS | 20 |
| 15 | P | | 275 / 60 | R 15 | | PAS | 20 |
| 15 | | 11 | L | - 15 | FI | AGR | 64 |
| 15 | | 11 | | - 15 | LT | T&B | 22 |
| 15 | | 11 | | R 15 | LT | T&B | 22 |
| 15 | | 11.00 | | - 15 | NHS | IND | 84 |
| 15 | | 11 | L | - 15 | SL | AGR | 68 |
| 15 | | 11.00 | | - 15 | TR | T&B | 28 |
| 15 | | 11.00 | | R 15 | TR | T&B | 28 |
| 15 | 36 | x | 11 | - 15 | NHS | IND | 76 |
| 15 | P | | 285 / 70 | - 15 | | PAS | 22 |
| 15 | P | | 285 / 70 | R 15 | | PAS | 22 |
| 15 | 31 | x | 11.50 | - 15 | LT | T&B | 22 |
| 15 | 31 | x | 11.50 | R 15 | LT | T&B | 22 |
| 15 | 32 | x | 11.5 | - 15 | | AIR | 24 |
| 15 | 32 | x | 11.50 | - 15 | LT | T&B | 24 |
| 15 | 32 | x | 11.50 | R 15 | LT | T&B | 24 |
| 15 | P | | 295 / 50 | - 15 | | PAS | 20 |
| 15 | P | | 295 / 50 | R 15 | | PAS | 20 |
| 15 | | | 300 | - 15 | | IND | 74 |
| 15 | | | 300 | - 15 | NHS | IND | 74 |
| 15 | | 12 | | - 15 | LT | T&B | 26 |
| 15 | | 12 | | R 15 | LT | T&B | 26 |
| 15 | 28 | x | 12 | - 15 | NHS | IND | 64 |
| 15 | 32 | x | 12 | - 15 | NHS | IND | 74 |
| 15 | | | 315 / 70 | R 15 | | IND | 74 |
| 15 | | 12.5 | L | - 15 | FI | A&I | 78 |
| 15 | | 12.5 | L | - 15 | SL | A&I | 78 |
| 15 | 25 | x | 12.50 | - 15 | NHS | A&I | 58 |
| 15 | 29 | x | 12.50 | - 15 | NHS | A&I | 68 |
| 15 | 31 | x | 12.50 | - 15 | NHS | A&I | 72 |
| 15 | 33 | x | 12.50 | - 15 | LT | T&B | 26 |
| 15 | 33 | x | 12.50 | R 15 | LT | T&B | 26 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------|------------|--------|-------|
| 15 | 33 | x 12.50 | - 15 | NHS | AGR | 78 |
| 15 | 35 | x 12.50 | - 15 | LT | T&B | 28 |
| 15 | 35 | x 12.50 | R 15 | LT | T&B | 28 |
| 15 | 36 | x 12.50 | - 15 | LT | T&B | 28 |
| 15 | 36 | x 12.50 | R 15 | LT | T&B | 28 |
| 15 | 37 | x 12.50 | - 15 | LT | T&B | 30 |
| 15 | 37 | x 12.50 | R 15 | LT | T&B | 30 |
| 15 | | N 50 | - 15 | | PAS | 22 |
| 15 | P | 325 / 50 | - 15 | | PAS | 24 |
| 15 | P | 325 / 50 | R 15 | | PAS | 24 |
| 15 | 28 | x 13 | - 15 | NHS | IND | 70 |
| 15 | | 13.50 | - 15 | FI | AGR | 80 |
| 15 | 31 | x 13.50 | - 15 | LT | T&B | 26 |
| 15 | 31 | x 13.50 | R 15 | LT | T&B | 26 |
| 15 | 31 | x 13.50 | - 15 | NHS | AGR | 80 |
| 15 | 36 | x 13.50 | - 15 | NHS | AGR | 94 |
| 15 | | 355 / 65 | - 15 | | IND | 88 |
| 15 | H 37 | x 14.0 | - 15 | | AIR | 34 |
| 15 | | 14.50 L | - 15 | NHS | IND | 98 |
| 15 | 35 | x 14.50 | - 15 | LT | T&B | 32 |
| 15 | 35 | x 14.50 | R 15 | LT | T&B | 32 |
| 15 | 36 | x 14.50 | - 15 | LT | T&B | 34 |
| 15 | 36 | x 14.50 | R 15 | LT | T&B | 34 |
| 15 | 37 | x 14.50 | - 15 | LT | T&B | 34 |
| 15 | 37 | x 14.50 | R 15 | LT | T&B | 34 |
| 15 | S | 375 / 60 | - 15 | | PAS | 32 |
| 15 | S | 375 / 60 | R 15 | | PAS | 32 |
| 15 | 32 | x 15 | - 15 | NHS | IND | 88 |
| 15 | 35 | x 15 | - 15 | NHS | IND | 100 |
| 15 | 31 | x 15.50 | - 15 | LT | T&B | 30 |
| 15 | 31 | x 15.50 | R 15 | LT | T&B | 30 |
| 15 | 31 | x 15.50 | - 15 | NHS | AGR | 92 |
| 15 | 39 | x 15.50 | - 15 | LT | T&B | 38 |
| 15 | 39 | x 15.50 | R 15 | LT | T&B | 38 |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | Tire Class | Ounces | Price |
|--------------|---|------------------|------|------------|--------|-------|
| 16 | M | 2.50 | - 16 | CYM | 4 | |
| 16 | M | 2.75 | - 16 | CYM | 6 | |
| 16 | M | 70 / 90 | - 16 | CYM | 4 | |
| 16 | M | 70 / 100 | - 16 | CYM | 6 | |
| 16 | M | 3.00 | - 16 | CYM | 6 | |
| 16 | M | 80 / 90 | - 16 | CYM | 6 | |
| 16 | M | 80 / 100 | - 16 | CYM | 6 | |
| 16 | M | 3.25 | - 16 | CYM | 6 | |
| 16 | M | 3.50 | - 16 | CYM | 6 | |
| 16 | M | 90 / 90 | - 16 | CYM | 6 | |
| 16 | M | 90 / 100 | - 16 | CYM | 6 | |
| 16 | M | 100 / 80 | - 16 | CYM | 8 | |
| 16 | M | 100 / 90 | - 16 | CYM | 8 | |
| 16 | M | 100 / 100 | - 16 | CYM | 8 | |
| 16 | T | 105 / 70 | - 16 | PAS | 8 | |
| 16 | T | 105 / 70 | R 16 | PAS | 8 | |
| 16 | M | P 75 | - 16 | CYM | 6 | |
| 16 | M | 110 / 80 | - 16 | CYM | 8 | |
| 16 | M | 110 / 80 | R 16 | CYM | 8 | |
| 16 | M | 110 / 90 | - 16 | CYM | 8 | |
| 16 | T | 115 / 70 | - 16 | PAS | 8 | |
| 16 | T | 115 / 70 | R 16 | PAS | 8 | |
| 16 | M | 4.60 | - 16 | CYM | 8 | |
| 16 | M | 120 / 70 | - 16 | CYM | 8 | |
| 16 | M | 120 / 80 | - 16 | CYM | 8 | |
| 16 | M | 120 / 80 | R 16 | CYM | 8 | |
| 16 | M | 120 / 90 | - 16 | CYM | 8 | |
| 16 | M | R 85 | - 16 | CYM | 8 | |
| 16 | T | 125 / 70 | - 16 | PAS | 8 | |
| 16 | T | 125 / 70 | R 16 | PAS | 8 | |
| 16 | T | 125 / 80 | - 16 | PAS | 8 | |
| 16 | T | 125 / 80 | R 16 | PAS | 8 | |
| 16 | T | 125 / 90 | - 16 | PAS | 10 | |
| 16 | T | 125 / 90 | R 16 | PAS | 10 | |
| 16 | M | 5.00 | - 16 | CYM | 10 | |
| 16 | M | 130 / 60 | R 16 | CYM | 8 | |
| 16 | M | 130 / 70 | - 16 | CYM | 10 | |
| 16 | M | 130 / 70 | R 16 | CYM | 10 | |
| 16 | M | 130 / 80 | - 16 | CYM | 10 | |
| 16 | M | 130 / 90 | - 15 | CYM | 10 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|------------------|------------|--------|-------|
| 16 | M 130 / 90 - 16 | CYM | 10 | |
| 16 | M 130 / 100 - 16 | CYM | 10 | |
| 16 | M T 90 - 16 | CYM | 10 | |
| 16 | T 135 / 70 - 16 | PAS | 10 | |
| 16 | T 135 / 70 R 16 | PAS | 10 | |
| 16 | 5.50 - 16 SL | AGR | 32 | |
| 16 | M 140 / 80 - 16 | CYM | 10 | |
| 16 | M 140 / 90 - 16 | CYM | 10 | |
| 16 | M 140 / 90 R 16 | CYM | 10 | |
| 16 | M U 90 - 16 | CYM | 10 | |
| 16 | T 145 / 80 - 16 | PAS | 10 | |
| 16 | T 145 / 80 R 16 | PAS | 10 | |
| 16 | T 145 / 90 - 16 | PAS | 10 | |
| 16 | T 145 / 90 R 16 | PAS | 10 | |
| 16 | M 150 / 80 - 16 | CYM | 12 | |
| 16 | M 150 / 80 R 16 | CYM | 12 | |
| 16 | M 150 / 90 - 16 | CYM | 12 | |
| 16 | 6 - 16 | AGR | 32 | |
| 16 | 6.00 - 16 LT | T&B | 14 | |
| 16 | 6.00 R 16 LT | T&B | 14 | |
| 16 | 6.00 - 16 NHS | IND | 34 | |
| 16 | 6.00 - 16 SL | AGR | 36 | |
| 16 | P 155 / 80 D 16 | PAS | 10 | |
| 16 | T 155 / 80 - 16 | PAS | 10 | |
| 16 | T 155 / 80 R 16 | PAS | 10 | |
| 16 | T 155 / 90 - 16 | PAS | 12 | |
| 16 | T 155 / 90 R 16 | PAS | 12 | |
| 16 | M 160 / 60 R 16 | CYM | 12 | |
| 16 | M 160 / 70 - 16 | CYM | 12 | |
| 16 | M 160 / 70 R 16 | CYM | 12 | |
| 16 | M 160 / 80 - 16 | CYM | 12 | |
| 16 | M 160 / 80 R 16 | CYM | 12 | |
| 16 | 6.50 - 16 LT | T&B | 14 | |
| 16 | 6.50 R 16 LT | T&B | 14 | |
| 16 | 6.50 - 16 SL | AGR | 40 | |
| 16 | 7.00 - 16 | IND | 46 | |
| 16 | 7.00 - 16 LT | T&B | 16 | |
| 16 | 7.00 R 16 LT | T&B | 16 | |
| 16 | 7.00 - 16 ML | T&B | 32 | |
| 16 | 7.50 - 16 | IND | 50 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|-----------|------|------------|--------|-------|
| 16 | | 7.50 | - 16 | LT | T&B | 18 |
| 16 | | 7.50 | R 16 | LT | T&B | 18 |
| 16 | | 7.50 | - 16 | SL | AGR | 48 |
| 16 | | 7.50 | - 16 | SS | IND | 52 |
| 16 | | F 78 | - 16 | LT | T&B | 14 |
| 16 | | 8.00 | - 16 | SL | AGR | 50 |
| 16 | P | 205 / 55 | R 16 | | PAS | 14 |
| 16 | | 8.3 | - 16 | | AGR | 50 |
| 16 | P | 215 / 60 | - 16 | | PAS | 14 |
| 16 | P | 215 / 60 | R 16 | | PAS | 14 |
| 16 | P | 215 / 70 | - 16 | | PAS | 16 |
| 16 | P | 215 / 70 | R 16 | | PAS | 16 |
| 16 | LT | 215 / 85 | - 16 | | T&B | 18 |
| 16 | LT | 215 / 85 | R 16 | | T&B | 18 |
| 16 | | H 78 | - 16 | LT | T&B | 18 |
| 16 | | 32 x 8.8 | | | AIR | 18 |
| 16 | P | 225 / 50 | - 16 | | PAS | 14 |
| 16 | P | 225 / 50 | R 16 | | PAS | 14 |
| 16 | P | 225 / 55 | R 16 | | PAS | 16 |
| 16 | P | 225 / 60 | - 16 | | PAS | 16 |
| 16 | P | 225 / 60 | R 16 | | PAS | 16 |
| 16 | LT | 225 / 75 | - 16 | | T&B | 18 |
| 16 | LT | 225 / 75 | R 16 | | T&B | 18 |
| 16 | P | 225 / 75 | - 16 | | PAS | 12 |
| 16 | P | 225 / 75 | R 16 | | PAS | 12 |
| 16 | | 9.00 | - 16 | | IND | 68 |
| 16 | | 9.00 | - 16 | DT | OTR | 64 |
| 16 | | 9.00 | R 16 | DT | OTR | 64 |
| 16 | | 9.00 | - 16 | LT | T&B | 24 |
| 16 | | 9.00 | R 16 | LT | T&B | 24 |
| 16 | | 9.00 | - 16 | SL | AGR | 58 |
| 16 | | 34 x 9.25 | - 16 | | AIR | 20 |
| 16 | P | 235 / 50 | - 16 | | PAS | 16 |
| 16 | P | 235 / 50 | R 16 | | PAS | 16 |
| 16 | P | 235 / 55 | R 16 | | PAS | 16 |
| 16 | P | 235 / 60 | - 16 | | PAS | 16 |
| 16 | P | 235 / 60 | R 16 | | PAS | 16 |
| 16 | P | 235 / 65 | R 16 | | PAS | 18 |
| 16 | P | 235 / 70 | - 16 | | PAS | 18 |
| 16 | P | 235 / 70 | R 16 | | PAS | 18 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|------------------|------------|--------|-------|
| 16 | LT 235 / 85 - 16 | T&B | 20 | |
| 16 | LT 235 / 85 R 16 | T&B | 20 | |
| 16 | L 78 - 16 LT | T&B | 18 | |
| 16 | L R 78 - 16 LT | T&B | 18 | |
| 16 | 9.5 - 16 | AGR | 60 | |
| 16 | 9.50 - 16 | AIR | 22 | |
| 16 | P 245 / 50 - 16 | PAS | 16 | |
| 16 | P 245 / 50 R 16 | PAS | 16 | |
| 16 | P 245 / 70 - 16 | PAS | 20 | |
| 16 | P 245 / 70 R 16 | PAS | 20 | |
| 16 | LT 245 / 75 - 16 | T&B | 20 | |
| 16 | LT 245 / 75 R 16 | T&B | 20 | |
| 16 | P 245 / 75 - 16 | PAS | 20 | |
| 16 | P 245 / 75 R 16 | PAS | 20 | |
| 16 | 10.00 - 16 SL | AGR | 72 | |
| 16 | P 255 / 45 R 16 | PAS | 16 | |
| 16 | P 255 / 50 - 16 | PAS | 18 | |
| 16 | P 255 / 50 R 16 | PAS | 18 | |
| 16 | LT 255 / 85 - 16 | T&B | 22 | |
| 16 | LT 255 / 85 R 16 | T&B | 22 | |
| 16 | P 265 / 50 - 16 | PAS | 18 | |
| 16 | P 265 / 50 R 16 | PAS | 18 | |
| 16 | P 265 / 75 - 16 | PAS | 22 | |
| 16 | P 265 / 75 R 16 | PAS | 22 | |
| 16 | P 275 / 50 - 16 | PAS | 20 | |
| 16 | P 275 / 50 R 16 | PAS | 20 | |
| 16 | P 275 / 70 - 16 | PAS | 22 | |
| 16 | P 275 / 70 R 16 | PAS | 22 | |
| 16 | 11.00 - 16 DT | OTR | 74 | |
| 16 | 11.00 R 16 DT | OTR | 74 | |
| 16 | 11 L - 16 SL | AGR | 70 | |
| 16 | 11.00 - 16 SL | AGR | 90 | |
| 16 | 36 x 11 | AIR | 26 | |
| 16 | P 285 / 70 - 16 | PAS | 24 | |
| 16 | P 285 / 70 R 16 | PAS | 24 | |
| 16 | LT 285 / 75 - 16 | T&B | 24 | |
| 16 | LT 285 / 75 R 16 | T&B | 24 | |
| 16 | 12.4 - 16 | AGR | 86 | |
| 16 | P 315 / 40 R 16 | PAS | 22 | |
| 16 | 12.50 - 16 | AIR | 32 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|---------|------|------------|--------|-------|
| 16 | | 12.5 | L | - 16 SL | AGR | 80 |
| 16 | 37 | x 13.0 | | - 16 | AIR | 32 |
| 16 | 39 | x 13 | | | AIR | 32 |
| 16 | | 13.6 | | - 16 | AGR | 94 |
| 16 | 40 | x 14 | | | AIR | 36 |
| 16 | | 15.00 | | - 16 | AIR | 42 |
| 16 | 42 | x 15 | | | AIR | 42 |
| 16 | 40 | x 15.5 | | - 16 | AIR | 40 |
| 16 | 40.5 | x 15.5 | | - 16 | AIR | 40 |
| 16 | | 16.00 | | - 16 DT | OTR | 114 |
| 16 | | 16.00 | | R 16 DT | OTR | 114 |
| 16 | | 17.00 | | - 16 | AIR | 50 |
| 16.1 | | 13.50 | | - 16.1 SL | AGR | 106 |
| 16.1 | | 14 | L | - 16.1 SL | AGR | 104 |
| 16.1 | | 14.5 | / 75 | - 16.1 SL | AGR | 104 |
| 16.1 | | 16.5 | L | - 16.1 SL | AGR | 132 |
| 16.1 | | 18.4 | | - 16.1 | AGR | 156 |
| 16.1 | | 19 | L | - 16.1 SL | AGR | 154 |
| 16.1 | 38 | x 20.00 | | - 16.1 NHS | AGR | 142 |
| 16.1 | | 21.5 | L | - 16.1 SL | AGR | 180 |
| 16.31 | 20 | x 1.75 | | | CYB | 6 |
| 16.31 | 20 | x 1.75 | / 47 | - 406 | CYB | 6 |
| 16.31 | 20 | x 2.125 | | | CYB | 8 |
| 16.48 | 20 | x 1 3/4 | | | CYB | 6 |
| 16.5 | | 8.00 | | - 16.5 LT | T&B | 16 |
| 16.5 | | 8.00 | | R 16.5 LT | T&B | 16 |
| 16.5 | | 8.75 | | - 16.5 LT | T&B | 18 |
| 16.5 | | 8.75 | | R 16.5 LT | T&B | 18 |
| 16.5 | | 9.50 | | - 16.5 LT | T&B | 20 |
| 16.5 | | 9.50 | | R 16.5 LT | T&B | 20 |
| 16.5 | 30 | x 9.50 | | - 16.5 LT | T&B | 18 |
| 16.5 | 30 | x 9.50 | | R 16.5 LT | T&B | 18 |
| 16.5 | | 10 | | - 16.5 LT | T&B | 20 |
| 16.5 | | 10 | | R 16.5 LT | T&B | 20 |
| 16.5 | | 10 | | - 16.5 NHS | IND | 60 |
| 16.5 | 31 | x 10.50 | | - 16.5 LT | T&B | 22 |
| 16.5 | 31 | x 10.50 | | R 16.5 LT | T&B | 22 |
| 16.5 | 31 | x 11.50 | | - 16.5 LT | T&B | 22 |
| 16.5 | 31 | x 11.50 | | R 16.5 LT | T&B | 22 |
| 16.5 | | 12 | | - 16.5 LT | T&B | 26 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | | Ounces | Price |
|--------------|------------------|---------|------------|-----|--------|-------|
| 16.5 | | 12 | R 16.5 | LT | T&B | 26 |
| 16.5 | | 12 | - 16.5 | NHS | IND | 76 |
| 16.5 | 33 | x 12.50 | - 16.5 | LT | T&B | 26 |
| 16.5 | 33 | x 12.50 | R 16.5 | LT | T&B | 26 |
| 16.5 | 36 | x 12.50 | - 16.5 | LT | T&B | 28 |
| 16.5 | 36 | x 12.50 | R 16.5 | LT | T&B | 28 |
| 16.5 | 37 | x 12.50 | - 16.5 | LT | T&B | 28 |
| 16.5 | 37 | x 12.50 | R 16.5 | LT | T&B | 28 |
| 16.5 | 36 | x 14.50 | - 16.5 | LT | T&B | 32 |
| 16.5 | 36 | x 14.50 | R 16.5 | LT | T&B | 32 |
| 16.5 | 37 | x 14.50 | - 16.5 | LT | T&B | 34 |
| 16.5 | 37 | x 14.50 | R 16.5 | LT | T&B | 34 |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | Tire Class | Ounces | Price |
|--------------|---|------------------|------|------------|--------|-------|
| 17 | M | 2.25 | - 17 | CYM | 4 | |
| 17 | M | 60 / 90 | - 17 | CYM | 4 | |
| 17 | M | 60 / 100 | - 17 | CYM | 4 | |
| 17 | M | 2.50 | - 17 | CYM | 4 | |
| 17 | M | 2.75 | - 17 | CYM | 6 | |
| 17 | M | 70 / 90 | - 17 | CYM | 6 | |
| 17 | M | 70 / 100 | - 17 | CYM | 6 | |
| 17 | M | 3.00 | - 17 | CYM | 6 | |
| 17 | M | 80 / 80 | - 17 | CYM | 6 | |
| 17 | M | 80 / 90 | - 17 | CYM | 6 | |
| 17 | M | 80 / 100 | - 17 | CYM | 6 | |
| 17 | M | 3.25 | - 17 | CYM | 6 | |
| 17 | M | 3.50 | - 17 | CYM | 8 | |
| 17 | M | 90 / 80 | - 17 | CYM | 6 | |
| 17 | M | 90 / 90 | - 17 | CYM | 6 | |
| 17 | M | 90 / 100 | - 17 | CYM | 6 | |
| 17 | M | 100 / 70 | - 17 | CYM | 8 | |
| 17 | M | 100 / 70 | R 17 | CYM | 8 | |
| 17 | M | 100 / 80 | - 17 | CYM | 8 | |
| 17 | M | 100 / 80 | R 17 | CYM | 8 | |
| 17 | M | 100 / 90 | - 17 | CYM | 8 | |
| 17 | M | 100 / 100 | - 17 | CYM | 8 | |
| 17 | M | 4.25 | - 17 | CYM | 8 | |
| 17 | M | 110 / 70 | - 17 | CYM | 8 | |
| 17 | M | 110 / 70 | R 17 | CYM | 8 | |
| 17 | M | 110 / 80 | - 17 | CYM | 8 | |
| 17 | M | 110 / 80 | R 17 | CYM | 8 | |
| 17 | M | 110 / 90 | - 17 | CYM | 8 | |
| 17 | M | 4.50 | - 17 | CYM | 10 | |
| 17 | M | 4.60 | - 17 | CYM | 8 | |
| 17 | M | 120 / 60 | R 17 | CYM | 8 | |
| 17 | M | 120 / 70 | - 17 | CYM | 8 | |
| 17 | M | 120 / 70 | R 17 | CYM | 8 | |
| 17 | M | 120 / 80 | - 17 | CYM | 8 | |
| 17 | M | 120 / 90 | - 17 | CYM | 10 | |
| 17 | M | 120 / 100 | - 17 | CYM | 10 | |
| 17 | M | 5.10 | - 17 | CYM | 10 | |
| 17 | M | 130 / 60 | R 17 | CYM | 10 | |
| 17 | M | 130 / 70 | - 17 | CYM | 10 | |
| 17 | M | 130 / 70 | R 17 | CYM | 10 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|---|------------------|-------|------|------------|--------|-------|
| 17 | M | 130 | / 80 | - 17 | CYM | 10 | |
| 17 | M | 130 | / 90 | - 17 | CYM | 10 | |
| 17 | M | 130 | / 100 | - 17 | CYM | 10 | |
| 17 | M | S | 90 | - 17 | CYM | 10 | |
| 17 | M | T | 90 | - 17 | CYM | 10 | |
| 17 | M | 140 | / 60 | R 17 | CYM | 10 | |
| 17 | M | 140 | / 70 | - 17 | CYM | 10 | |
| 17 | M | 140 | / 70 | R 17 | CYM | 10 | |
| 17 | M | 140 | / 80 | - 17 | CYM | 10 | |
| 17 | M | 140 | / 80 | R 17 | CYM | 10 | |
| 17 | M | 150 | / 60 | R 17 | CYM | 10 | |
| 17 | M | 150 | / 70 | - 17 | CYM | 12 | |
| 17 | M | 150 | / 70 | R 17 | CYM | 12 | |
| 17 | M | 150 | / 90 | - 17 | CYM | 12 | |
| 17 | | 6.00 | | - 17 | T&B | 12 | |
| 17 | | 6.00 | | R 17 | T&B | 12 | |
| 17 | T | 155 | / 70 | - 17 | PAS | 10 | |
| 17 | T | 155 | / 70 | R 17 | PAS | 10 | |
| 17 | M | 160 | / 60 | - 17 | CYM | 12 | |
| 17 | M | 160 | / 60 | R 17 | CYM | 12 | |
| 17 | M | 160 | / 70 | - 17 | CYM | 12 | |
| 17 | M | 170 | / 60 | - 17 | CYM | 12 | |
| 17 | M | 170 | / 60 | R 17 | CYM | 12 | |
| 17 | | 7.00 | | - 17 | T&B | 18 | |
| 17 | | 7.00 | | R 17 | T&B | 18 | |
| 17 | M | 180 | / 50 | R 17 | CYM | 12 | |
| 17 | M | 180 | / 55 | R 17 | CYM | 12 | |
| 17 | M | 180 | / 60 | R 17 | CYM | 14 | |
| 17 | | 7.50 | | - 17 | T&B | 18 | |
| 17 | | 7.50 | | R 17 | T&B | 18 | |
| 17 | | 8.25 | | - 17 | T&B | 20 | |
| 17 | | 8.25 | | R 17 | T&B | 20 | |
| 17 | | 225 | / 50 | R 17 | PAS | 14 | |
| 17 | P | 245 | / 40 | R 17 | PAS | 16 | |
| 17 | P | 245 | / 45 | R 17 | PAS | 16 | |
| 17 | P | 255 | / 45 | R 17 | PAS | 18 | |
| 17 | P | 275 | / 40 | R 17 | PAS | 18 | |
| 17 | P | 285 | / 35 | R 17 | PAS | 18 | |
| 17 | P | 285 | / 40 | R 17 | PAS | 20 | |
| 17 | P | 315 | / 35 | R 17 | PAS | 22 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------------|------------|--------|-------|
| 17 | P | 335 / 35 | R 17 | PAS | 22 | |
| 17 | C 40 | x 18.0 | - 17 | AIR | 46 | |
| 17.5 | | 7 | - 17.5 LT | T&B | 14 | |
| 17.5 | | 7 | R 17.5 LT | T&B | 14 | |
| 17.5 | | 8 | R 17.5 HC | T&B | 16 | |
| 17.5 | | 8 | - 17.5 LT | T&B | 16 | |
| 17.5 | | 8 | R 17.5 LT | T&B | 16 | |
| 17.5 | | 215 / 75 | R 17.5 | IND | 50 | |
| 17.5 | | 215 / 75 | R 17.5 HC | T&B | 16 | |
| 17.5 | | 9 | R 17.5 HC | T&B | 20 | |
| 17.5 | | 235 / 75 | R 17.5 | IND | 56 | |
| 17.5 | | 9.5 | R 17.5 | IND | 60 | |
| 17.5 | | 245 / 70 | R 17.5 | IND | 58 | |
| 17.5 | | 10 | R 17.5 HC | T&B | 24 | |
| 17.5 | | 10 | - 17.5 LT | T&B | 22 | |
| 17.5 | | 10 | R 17.5 LT | T&B | 22 | |
| 17.5 | | 275 / 65 | R 17.5 HC | T&B | 22 | |
| 17.5 | | 11 | R 17.5 HC | T&B | 26 | |
| 17.5 | | 14 | - 17.5 | T&B | 32 | |
| 17.5 | | 14 | R 17.5 | T&B | 32 | |
| 17.5 | | 14 | - 17.5 ML | T&B | 64 | |
| 17.5 | | 14 | - 17.5 NHS | IND | 94 | |
| 17.5 | 36 | x 16 | - 17.5 NHS | AGR | 110 | |
| 17.72 | CT | 205 / 45 | R 450 | PAS | 14 | |
| 17.75 | 20 | x 1.25 | | CYB | 4 | |
| 17.75 | 20 | x 1 1/4 | | CYB | 4 | |
| 17.75 | 20 | x 1.375 | | CYB | 4 | |
| 17.75 | 20 | x 1 3/8 | | CYB | 4 | |
| 18 | M | 2.50 | - 18 | CYM | 4 | |
| 18 | M | 2.75 | - 18 | CYM | 6 | |
| 18 | M | 70 / 90 | - 18 | CYM | 6 | |
| 18 | M | 70 / 100 | - 18 | CYM | 6 | |
| 18 | M | 3.00 | - 18 | CYM | 6 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|---|------------------|-------|------|------------|--------|-------|
| 18 | M | 80 | / 80 | - 18 | CYM | 6 | |
| 18 | M | 80 | / 90 | - 18 | CYM | 6 | |
| 18 | M | 80 | / 100 | - 18 | CYM | 6 | |
| 18 | M | 3.25 | | - 18 | CYM | 8 | |
| 18 | M | 3.50 | | - 18 | CYM | 8 | |
| 18 | M | 90 | / 80 | - 18 | CYM | 6 | |
| 18 | M | 90 | / 90 | - 18 | CYM | 6 | |
| 18 | M | 90 | / 100 | - 18 | CYM | 8 | |
| 18 | M | J | 90 | - 18 | CYM | 6 | |
| 18 | M | L | 90 | - 18 | CYM | 8 | |
| 18 | M | M | 90 | - 18 | CYM | 8 | |
| 18 | M | 100 | / 80 | - 18 | CYM | 8 | |
| 18 | M | 100 | / 90 | - 18 | CYM | 8 | |
| 18 | M | 100 | / 100 | - 18 | CYM | 8 | |
| 18 | | 4.00 | | - 18 | SL AGR | 22 | |
| 18 | M | 4.00 | | - 18 | CYM | 8 | |
| 18 | M | 4.10 | | - 18 | CYM | 8 | |
| 18 | M | 4.25 | | - 18 | CYM | 10 | |
| 18 | M | 4.25 | / 85 | - 18 | CYM | 8 | |
| 18 | M | 110 | / 70 | - 18 | CYM | 8 | |
| 18 | M | 110 | / 70 | R 18 | CYM | 8 | |
| 18 | M | 110 | / 80 | - 18 | CYM | 8 | |
| 18 | M | 110 | / 80 | R 18 | CYM | 8 | |
| 18 | M | 110 | / 90 | - 18 | CYM | 8 | |
| 18 | M | 110 | / 100 | - 18 | CYM | 8 | |
| 18 | M | N | 90 | - 18 | CYM | 8 | |
| 18 | M | P | 85 | - 18 | CYM | 8 | |
| 18 | M | P | 90 | - 18 | CYM | 10 | |
| 18 | M | 4.60 | | - 18 | CYM | 10 | |
| 18 | M | 120 | / 60 | R 18 | CYM | 8 | |
| 18 | M | 120 | / 70 | - 18 | CYM | 8 | |
| 18 | M | 120 | / 80 | - 18 | CYM | 10 | |
| 18 | M | 120 | / 90 | - 18 | CYM | 10 | |
| 18 | M | 120 | / 100 | - 18 | CYM | 10 | |
| 18 | M | R | 90 | - 18 | CYM | 10 | |
| 18 | M | 5.10 | | - 18 | CYM | 10 | |
| 18 | M | 130 | / 60 | - 18 | CYM | 10 | |
| 18 | M | 130 | / 60 | R 18 | CYM | 10 | |
| 18 | M | 130 | / 70 | - 18 | CYM | 10 | |
| 18 | M | 130 | / 80 | - 18 | CYM | 10 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|------------------|------------|--------|-------|
| 18 | M 130 / 80 R 18 | CYM | 10 | |
| 18 | M 130 / 90 - 18 | CYM | 10 | |
| 18 | M 130 / 100 - 18 | CYM | 10 | |
| 18 | M S 85 - 18 | CYM | 10 | |
| 18 | M T 85 - 18 | CYM | 10 | |
| 18 | M 140 / 60 - 18 | CYM | 10 | |
| 18 | M 140 / 60 R 18 | CYM | 10 | |
| 18 | M 140 / 70 - 18 | CYM | 10 | |
| 18 | M 140 / 70 R 18 | CYM | 10 | |
| 18 | M 140 / 80 - 18 | CYM | 10 | |
| 18 | M 150 / 60 - 18 | CYM | 12 | |
| 18 | M 150 / 60 R 18 | CYM | 12 | |
| 18 | M 150 / 70 - 18 | CYM | 12 | |
| 18 | M 150 / 70 R 18 | CYM | 12 | |
| 18 | T 155 / 80 - 18 | PAS | 12 | |
| 18 | T 155 / 80 R 18 | PAS | 12 | |
| 18 | M 160 / 60 - 18 | CYM | 12 | |
| 18 | M 160 / 60 R 18 | CYM | 12 | |
| 18 | M 160 / 70 - 18 | CYM | 12 | |
| 18 | M 170 / 60 - 18 | CYM | 14 | |
| 18 | M 170 / 60 R 18 | CYM | 12 | |
| 18 | 7.00 - 18 | T&B | 22 | |
| 18 | 7.00 R 18 | T&B | 22 | |
| 18 | M 180 / 50 R 18 | CYM | 12 | |
| 18 | M 180 / 55 R 18 | CYM | 14 | |
| 18 | 7.50 - 18 | T&B | 24 | |
| 18 | 7.50 R 18 | T&B | 24 | |
| 18 | 7.50 - 18 NHS | IND | 58 | |
| 18 | 7.50 - 18 SL | AGR | 52 | |
| 18 | P 275 / 35 R 18 | PAS | 18 | |
| 18 | 40 x 12 | AIR | 32 | |
| 18 | P 335 / 35 R 18 | PAS | 22 | |
| 18 | 41 x 15.0 - 18 | AIR | 40 | |
| 18 | 44 x 16 | AIR | 44 | |
| 18 | 44.5 x 16.5 - 18 | AIR | 48 | |
| 18.5 | 13 - 18.5 NHS | IND | 36 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------|------------------|--------|------------|--------|-------|
| 19 | M | 2.50 | - 19 | CYM | 6 | |
| 19 | M | 70 / 100 | - 19 | CYM | 6 | |
| 19 | M | 3.00 | - 19 | CYM | 6 | |
| 19 | M | 80 / 80 | - 19 | CYM | 6 | |
| 19 | M | 80 / 90 | - 19 | CYM | 6 | |
| 19 | M | 80 / 100 | - 19 | CYM | 6 | |
| 19 | M | 3.25 | - 19 | CYM | 8 | |
| 19 | M | 3.50 | - 19 | CYM | 8 | |
| 19 | M | 90 / 80 | - 19 | CYM | 8 | |
| 19 | M | 90 / 90 | - 19 | CYM | 8 | |
| 19 | M | 90 / 100 | - 19 | CYM | 8 | |
| 19 | M | J 90 | - 19 | CYM | 8 | |
| 19 | M | L 90 | - 19 | CYM | 8 | |
| 19 | M | M 90 | - 19 | CYM | 8 | |
| 19 | M | 100 / 80 | - 19 | CYM | 8 | |
| 19 | M | 100 / 90 | - 19 | CYM | 8 | |
| 19 | M | 100 / 100 | - 19 | CYM | 8 | |
| 19 | | 4.00 | - 19 | SL AGR | 24 | |
| 19 | M | 4.10 | - 19 | CYM | 8 | |
| 19 | M | 110 / 80 | - 19 | CYM | 8 | |
| 19 | M | 110 / 90 | - 19 | CYM | 8 | |
| 19 | M | 110 / 100 | - 19 | CYM | 10 | |
| 19 | M | 120 / 80 | - 19 | CYM | 10 | |
| 19 | M | 120 / 90 | - 19 | CYM | 10 | |
| 19 | M | 120 / 100 | - 19 | CYM | 10 | |
| 19 | M | 130 / 80 | - 19 | CYM | 10 | |
| 19 | M | 140 / 80 | - 19 | CYM | 12 | |
| 19 | H 40 | x 14.0 | - 19 | AIR | 36 | |
| 19 | H 40 | x 14.5 | - 19 | AIR | 38 | |
| 19 | H 42 | x 16.0 | - 19 | AIR | 44 | |
| 19.5 | | 8 | - 19.5 | T&B | 22 | |
| 19.5 | | 8 | R 19.5 | T&B | 22 | |
| 19.5 | | 225 / 70 | R 19.5 | T&B | 24 | |
| 19.5 | | 245 / 70 | R 19.5 | T&B | 26 | |
| 19.5 | | 245 / 70 | R 19.5 | IND | 62 | |
| 19.5 | | 265 / 70 | R 19.5 | IND | 70 | |
| 19.5 | | 285 / 70 | R 19.5 | IND | 76 | |
| 19.5 | | 15 | - 19.5 | T&B | 48 | |
| 19.5 | | 15 | R 19.5 | T&B | 48 | |
| 19.5 | | 15 | - 19.5 | ML T&B | 98 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|------|--------|------------|--------|-------|
| 19.5 | | 15 | - 19.5 | NHS | IND | 118 |
| 19.5 | | 16.5 | - 19.5 | | T&B | 56 |
| 19.5 | | 16.5 | R 19.5 | | T&B | 56 |
| 19.5 | | 16.5 | - 19.5 | ML | T&B | 112 |
| 19.5 | | 18 | - 19.5 | | T&B | 60 |
| 19.5 | | 18 | R 19.5 | | T&B | 60 |
| 19.5 | | 18 | - 19.5 | ML | T&B | 122 |
| 19.5 | 40 | x 19 | - 19.5 | NHS | AGR | 144 |
| 19.5 | | 19.5 | - 19.5 | | T&B | 70 |
| 19.5 | | 19.5 | R 19.5 | | T&B | 70 |
| 19.5 | | 19.5 | - 19.5 | ML | T&B | 140 |
| 19.5 | | 22.5 | - 19.5 | ML | T&B | 160 |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------------|--------|-------|
| 20 | 7.00 | - 20 | IND | 54 | |
| 20 | 7.00 | - 20 ML | T&B | 46 | |
| 20 | 7.50 | - 20 | T&B | 26 | |
| 20 | 7.50 | - 20 | IND | 60 | |
| 20 | 7.50 | R 20 | T&B | 26 | |
| 20 | 7.50 | - 20 ML | T&B | 50 | |
| 20 | 7.50 | - 20 SL | AGR | 54 | |
| 20 | 8.25 | - 20 | T&B | 28 | |
| 20 | 8.25 | - 20 | IND | 70 | |
| 20 | 8.25 | R 20 | T&B | 28 | |
| 20 | 8.25 | - 20 ML | T&B | 58 | |
| 20 | 8.25 | - 20 NHS | OTR | 70 | |
| 20 | 9.00 | - 20 | T&B | 34 | |
| 20 | 9.00 | - 20 | IND | 80 | |
| 20 | 9.00 | R 20 | T&B | 34 | |
| 20 | 9.00 | - 20 ML | T&B | 66 | |
| 20 | 9.00 | - 20 NHS | OTR | 80 | |
| 20 | 9.50 | - 20 SL | AGR | 74 | |
| 20 | 10.00 | - 20 | T&B | 36 | |
| 20 | 10.00 | - 20 | IND | 88 | |
| 20 | 10.00 | R 20 | T&B | 36 | |
| 20 | 10.00 | - 20 ML | T&B | 74 | |
| 20 | 10.00 | - 20 NHS | OTR | 90 | |
| 20 | 10.00 | - 20 TG | OTR | 88 | |
| 20 | 275 / 85 | D 20 | IND | 80 | |
| 20 | 11.00 | - 20 | T&B | 40 | |
| 20 | 11.00 | - 20 | IND | 96 | |
| 20 | 11.00 | R 20 | T&B | 40 | |
| 20 | 11.00 | - 20 ML | T&B | 80 | |
| 20 | 11.00 | - 20 NHS | OTR | 98 | |
| 20 | 11.1 | - 20 | T&B | 36 | |
| 20 | 11.50 | - 20 | T&B | 40 | |
| 20 | 11.50 | R 20 | T&B | 40 | |
| 20 | 11.9 | - 20 | T&B | 40 | |
| 20 | 12.00 | - 20 | T&B | 44 | |
| 20 | 12.00 | - 20 | IND | 106 | |
| 20 | 12.00 | R 20 | T&B | 44 | |
| 20 | 12.00 | - 20 ML | T&B | 88 | |
| 20 | 12.00 | - 20 NHS | OTR | 108 | |
| 20 | 12.00 | R 20 NHS | OTR | 108 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------------|--------|-------|
| 20 | 315 / 80 | D 20 | IND | 94 | |
| 20 | 13.00 | - 20 | IND | 118 | |
| 20 | 13.00 | - 20 | T&B | 50 | |
| 20 | 13.00 | R 20 | T&B | 50 | |
| 20 | 13.00 | - 20 ML | T&B | 100 | |
| 20 | 13.00 | - 20 TG | OTR | 116 | |
| 20 | 345 / 80 | D 20 | IND | 110 | |
| 20 | 355 / 80 | D 20 | IND | 114 | |
| 20 | 14.00 | - 20 | T&B | 58 | |
| 20 | 14.00 | R 20 | T&B | 58 | |
| 20 | 14.00 | - 20 DT | OTR | 134 | |
| 20 | 14.00 | R 20 DT | OTR | 134 | |
| 20 | 14.00 | - 20 ML | T&B | 116 | |
| 20 | 14.00 | R 20 ML | T&B | 116 | |
| 20 | 14.00 | - 20 NHS | OTR | 140 | |
| 20 | 14.00 | R 20 NHS | OTR | 140 | |
| 20 | 14.00 | - 20 TG | OTR | 140 | |
| 20 | 14 / 80 | R 20 | IND | 112 | |
| 20 | 38 x 14.00 | - 20 NHS | AGR | 104 | |
| 20 | 15.50 | - 20 | AIR | 46 | |
| 20 | 16.00 | R 20 | T&B | 68 | |
| 20 | 16.00 | - 20 DT | OTR | 168 | |
| 20 | 16.00 | R 20 DT | OTR | 168 | |
| 20 | 46 x 16 | - 20 | AIR | 46 | |
| 20 | H 44.5 x 16.5 | - 20 | AIR | 48 | |
| 20 | 425 / 95 | R 20 | OTR | 162 | |
| 20 | 17.00 | - 20 | AIR | 54 | |
| 20 | H 45 x 17.0 | - 20 | AIR | 48 | |
| 20 | 49 x 17 | - 20 | AIR | 54 | |
| 20 | 38 x 18.00 | - 20 NHS | AGR | 134 | |
| 20 | 44 x 18.00 | - 20 NHS | AGR | 154 | |
| 20 | 44 x 18 | - 20 NHS | IND | 150 | |
| 20 | H 46 x 18.0 | - 20 | AIR | 52 | |
| 20 | 49 x 19.0 | - 20 | AIR | 60 | |
| 20 | 50 x 20.0 | - 20 | AIR | 64 | |
| 20 | 56 x 20.0 | - 20 | AIR | 72 | |
| 20 | 52 x 20.5 | - 20 | AIR | 68 | |
| 20 | 50 x 21.0 | - 20 | AIR | 66 | |
| 20 | 42 x 25.00 | - 20 NHS | AGR | 196 | |
| 20 | 48 x 25.00 | - 20 NHS | AGR | 232 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|--------------|-------|------------|--------|-------|
| 20 | 48 | x 31.00 | - 20 | NHS | AGR | 282 |
| 20 | 44 | x 41.00 | - 20 | NHS | AGR | 332 |
| 20.30 | 24 | x 2.125 | | | CYB | 8 |
| 20.30 | 24 | x 2.125 / 57 | - 507 | | CYB | 8 |
| 20.31 | 24 | x 1.75 | | | CYB | 6 |
| 20.31 | 24 | x 2.125 | | | CYB | 8 |
| 20.48 | 24 | x 1 3/4 | | | CYB | 6 |
| | | | | | | |
| 21 | M | 2.50 | - 21 | | CYM | 6 |
| 21 | M | 2.75 | - 21 | | CYM | 6 |
| 21 | M | 70 / 90 | - 21 | | CYM | 6 |
| 21 | M | 3.00 | - 21 | | CYM | 6 |
| 21 | M | 80 / 90 | - 21 | | CYM | 6 |
| 21 | M | 80 / 100 | - 21 | | CYM | 6 |
| 21 | M | H 90 | - 21 | | CYM | 6 |
| 21 | M | 90 / 90 | - 21 | | CYM | 8 |
| 21 | M | 100 / 90 | - 21 | | CYM | 8 |
| 21 | M | 100 / 100 | - 21 | | CYM | 8 |
| 21 | | 12.00 | - 21 | ML | T&B | 88 |
| 21 | | 12.00 | - 21 | NHS | OTR | 106 |
| 21 | | 12.00 | R 21 | NHS | OTR | 106 |
| 21 | | 14.00 | R 21 | | T&B | 58 |
| 21 | | 14.00 | - 21 | ML | T&B | 116 |
| 21 | | 14.00 | R 21 | ML | T&B | 116 |
| 21 | | 14.00 | - 21 | NHS | OTR | 140 |
| 21 | | 14.00 | R 21 | NHS | OTR | 140 |
| 21 | C 40 | x 14.0 | - 21 | | AIR | 36 |
| 21 | | 14.5 | - 21 | | T&B | 60 |
| 21 | | 16.00 | R 21 | | T&B | 68 |
| 21 | | 16.00 | - 21 | NHS | OTR | 176 |
| 21 | | 16.00 | R 21 | NHS | OTR | 176 |
| 21 | | 18 | - 21 | ML | T&B | 132 |
| 21 | | 23 | - 21 | ML | T&B | 188 |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|---|-------|------------|--------|-------|
| 21 | 24 | - | 21 DT | OTR | 244 | |
| 21 | 24 | R | 21 DT | OTR | 244 | |
| 21 | 27.25 | - | 21 DT | OTR | 302 | |
| 21 | 27.25 | R | 21 DT | OTR | 302 | |
| 21.24 | 24 | x | 1 3/8 | CYB | 6 | |
| 21.52 | 24 | x | 1 1/4 | CYB | 6 | |
| 21.75 | 24 | x | 1.25 | CYB | 6 | |
| 21.75 | 24 | x | 1.375 | CYB | 6 | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|-----------------|------------|--------|-------|
| 22 | | 10.00 - 22 | T&B | 38 | |
| 22 | | 10.00 R 22 | T&B | 38 | |
| 22 | | 10.00 - 22 ML | T&B | 76 | |
| 22 | | 11.00 - 22 | T&B | 42 | |
| 22 | | 11.00 R 22 | T&B | 42 | |
| 22 | | 11.00 - 22 ML | T&B | 84 | |
| 22 | H 49 | x 19.0 - 22 | AIR | 60 | |
| 22.31 | 26 | x 1.75 | CYB | 8 | |
| 22.31 | 26 | x 2.10 | CYB | 8 | |
| 22.31 | 26 | x 2.125 | CYB | 8 | |
| 22.48 | 26 | x 1 3/4 | CYB | 8 | |
| 22.5 | | 8 - 22.5 | T&B | 24 | |
| 22.5 | | 8 R 22.5 | T&B | 24 | |
| 22.5 | | 9 - 22.5 | T&B | 28 | |
| 22.5 | | 9 R 22.5 | T&B | 28 | |
| 22.5 | | 9 - 22.5 ML | T&B | 56 | |
| 22.5 | | 245 / 75 - 22.5 | T&B | 30 | |
| 22.5 | | 245 / 75 R 22.5 | T&B | 30 | |
| 22.5 | | 250 / 70 R 22.5 | T&B | 30 | |
| 22.5 | | 10 - 22.5 | T&B | 32 | |
| 22.5 | | 10 R 22.5 | T&B | 32 | |
| 22.5 | | 10 - 22.5 ML | T&B | 66 | |
| 22.5 | | 10 - 22.5 NHS | OTR | 78 | |
| 22.5 | | 265 / 75 - 22.5 | T&B | 32 | |
| 22.5 | | 265 / 75 R 22.5 | T&B | 32 | |
| 22.5 | | 11 - 22.5 | T&B | 36 | |
| 22.5 | | 11 R 22.5 | T&B | 36 | |
| 22.5 | | 11 - 22.5 ML | T&B | 74 | |
| 22.5 | | 11 - 22.5 NHS | OTR | 88 | |
| 22.5 | | 295 / 75 - 22.5 | T&B | 38 | |
| 22.5 | | 295 / 75 R 22.5 | T&B | 38 | |
| 22.5 | | 12 - 22.5 | T&B | 40 | |
| 22.5 | | 12 R 22.5 | T&B | 40 | |
| 22.5 | | 12 - 22.5 ML | T&B | 82 | |
| 22.5 | | 12 - 22.5 NHS | OTR | 98 | |
| 22.5 | | 305 / 75 R 22.5 | T&B | 40 | |
| 22.5 | | 315 / 80 R 22.5 | T&B | 42 | |
| 22.5 | | 12.5 - 22.5 | T&B | 40 | |
| 22.5 | | 12.5 R 22.5 | T&B | 40 | |
| 22.5 | | 12.75 - 22.5 | T&B | 42 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|------------|------------|--------|-------|
| 22.5 | 12.75 | R 22.5 | T&B | 42 | |
| 22.5 | 13 | - 22.5 | T&B | 44 | |
| 22.5 | 13 | - 22.5 NHS | OTR | 108 | |
| 22.5 | 15 | - 22.5 | T&B | 52 | |
| 22.5 | 15 | R 22.5 | T&B | 52 | |
| 22.5 | 15 | - 22.5 ML | T&B | 104 | |
| 22.5 | 385 / 65 | R 22.5 | T&B | 52 | |
| 22.5 | 16.5 | - 22.5 | T&B | 60 | |
| 22.5 | 16.5 | R 22.5 | T&B | 60 | |
| 22.5 | 16.5 | - 22.5 ML | T&B | 120 | |
| 22.5 | 425 / 65 | R 22.5 | T&B | 58 | |
| 22.5 | 445 / 65 | R 22.5 | T&B | 64 | |
| 22.5 | 18 | - 22.5 | T&B | 66 | |
| 22.5 | 18 | R 22.5 | T&B | 66 | |
| 22.5 | 18 | - 22.5 ML | T&B | 132 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | Tire Class | Ounces | Price |
|--------------|------------------|----------|-----------|------------|--------|-------|
| 23 | 52 | x 20.5 | - 23 | AIR | 68 | |
| 23.24 | 26 | x 1 3/8 | | CYB | 6 | |
| 23.5 | | 23 | - 23.5 ML | T&B | 188 | |
| 23.51 | 26 | x 1 1/4 | | CYB | 6 | |
| 23.75 | 26 | x 1.25 | | CYB | 6 | |
| 23.75 | 26 | x 1.375 | | CYB | 6 | |
| | | | | | | |
| | | | | | | |
| 24 | | 7.50 | - 24 SL | AGR | 66 | |
| 24 | | 8.3 | - 24 | AGR | 62 | |
| 24 | | 9.00 | - 24 SL | AGR | 88 | |
| 24 | | 9.5 | - 24 | AGR | 74 | |
| 24 | | 10.00 | - 24 ML | T&B | 80 | |
| 24 | | 10.00 | - 24 TG | OTR | 96 | |
| 24 | | 10.00 | R 24 TG | OTR | 96 | |
| 24 | | 11.00 | - 24 | T&B | 44 | |
| 24 | | 11.00 | R 24 | T&B | 44 | |
| 24 | | 11.00 | - 24 ML | T&B | 86 | |
| 24 | | 11.00 | - 24 SL | AGR | 108 | |
| 24 | | 11.2 | - 24 | AGR | 92 | |
| 24 | | 11.25 | - 24 SL | AGR | 112 | |
| 24 | | 12.00 | - 24 | T&B | 48 | |
| 24 | | 12.00 | - 24 | IND | 116 | |
| 24 | | 12.00 | R 24 | T&B | 48 | |
| 24 | | 12.00 | - 24 ML | T&B | 96 | |
| 24 | | 12.00 | - 24 NHS | OTR | 118 | |
| 24 | | 12.00 | R 24 NHS | OTR | 118 | |
| 24 | | 12.00 | - 24 TG | OTR | 112 | |
| 24 | | 12.00 | R 24 TG | OTR | 112 | |
| 24 | | 12.4 | - 24 | AGR | 108 | |
| 24 | | 320 / 70 | R 24 | AGR | 100 | |
| 24 | | 13.00 | - 24 | IND | 128 | |
| 24 | | 13.00 | - 24 ML | T&B | 108 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|-----------|------------|--------|-------|
| 24 | 13.00 | R 24 ML | T&B | 108 | |
| 24 | 13.00 | - 24 NHS | OTR | 134 | |
| 24 | 13.00 | R 24 NHS | OTR | 134 | |
| 24 | 13.00 | - 24 TG | OTR | 132 | |
| 24 | 13.00 | R 24 TG | OTR | 128 | |
| 24 | 13.6 | - 24 | AGR | 122 | |
| 24 | 14.00 | - 24 | T&B | 62 | |
| 24 | 14.00 | - 24 | IND | 148 | |
| 24 | 14.00 | R 24 | T&B | 62 | |
| 24 | 14.00 | - 24 ML | T&B | 126 | |
| 24 | 14.00 | R 24 ML | T&B | 126 | |
| 24 | 14.00 | - 24 NHS | OTR | 150 | |
| 24 | 14.00 | R 24 NHS | OTR | 150 | |
| 24 | 14.00 | - 24 TG | OTR | 152 | |
| 24 | 14.00 | R 24 TG | OTR | 148 | |
| 24 | 360 / 70 | R 24 | AGR | 116 | |
| 24 | 14.9 | - 24 | AGR | 140 | |
| 24 | 380 / 70 | R 24 | AGR | 128 | |
| 24 | 385 / 95 | R 24 | OTR | 152 | |
| 24 | 16.00 | - 24 DT | OTR | 198 | |
| 24 | 16.00 | R 24 DT | OTR | 198 | |
| 24 | 16.00 | - 24 TG | OTR | 182 | |
| 24 | 16.00 | R 24 TG | OTR | 182 | |
| 24 | 420 / 70 | R 24 | AGR | 148 | |
| 24 | 16.9 | - 24 | AGR | 168 | |
| 24 | 16.9 | R 24 | AGR | 168 | |
| 24 | 17.5 L | - 24 | AGR | 164 | |
| 24 | 18.00 | - 24 DT | OTR | 212 | |
| 24 | 18.00 | R 24 DT | OTR | 212 | |
| 24 | 18.4 | - 24 | AGR | 192 | |
| 24 | 19.5 L | - 24 | AGR | 190 | |
| 24 | 21 L | - 24 | AGR | 220 | |
| 24 | H 54 x 21.0 | - 24 | AIR | 72 | |
| 24.49 | 700 x 28 | | CYB | 6 | |
| 24.5 | 245 / 75 | - 24.5 | T&B | 34 | |
| 24.5 | 245 / 75 | R 24.5 | T&B | 34 | |
| 24.5 | 11 | - 24.5 | T&B | 38 | |
| 24.5 | 11 | R 24.5 | T&B | 38 | |
| 24.5 | 11 | - 24.5 ML | T&B | 78 | |
| 24.5 | 285 / 75 | - 24.5 | T&B | 38 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|---------|------------|--------|-------|
| 24.5 | 285 / 75 R 24.5 | | T&B | 38 | |
| 24.5 | 12 - 24.5 | | T&B | 42 | |
| 24.5 | 12 R 24.5 | | T&B | 42 | |
| 24.5 | 13.5 - 24.5 | | T&B | 50 | |
| 24.5 | 13.5 R 24.5 | | T&B | 50 | |
| 24.79 | 27 | × 1 | CYB | 4 | |
| 24.79 | 27 | × 1 1/8 | CYB | 6 | |
| 24.79 | 27 | × 1 1/4 | CYB | 6 | |
| 24.79 | 27 | × 1 1/4 | HP CYB | 6 | |
| | | | | | |
| 25 | 11.00 - 25 ML | | T&B | 88 | |
| 25 | 12.00 - 25 ML | | T&B | 96 | |
| 25 | 12.00 - 25 NHS | | OTR | 116 | |
| 25 | 12.00 R 25 NHS | | OTR | 116 | |
| 25 | 13.00 - 25 ML | | T&B | 112 | |
| 25 | 13.00 - 25 NHS | | OTR | 134 | |
| 25 | 13.00 R 25 NHS | | OTR | 134 | |
| 25 | 14.00 - 25 ML | | T&B | 126 | |
| 25 | 14.00 R 25 ML | | T&B | 126 | |
| 25 | 14.00 - 25 NHS | | OTR | 150 | |
| 25 | 14.00 R 25 NHS | | OTR | 150 | |
| 25 | 385 / 95 R 25 | | OTR | 152 | |
| 25 | 15.5 - 25 | | OTR | 152 | |
| 25 | 15.5 R 25 | | OTR | 152 | |
| 25 | 16.00 - 25 | | OTR | 188 | |
| 25 | 16.00 - 25 | | IND | 188 | |
| 25 | 16.00 R 25 | | OTR | 188 | |
| 25 | 17.5 - 25 | | OTR | 176 | |
| 25 | 17.5 R 25 | | OTR | 176 | |
| 25 | 445 / 80 R 25 | | OTR | 180 | |
| 25 | 445 / 95 R 25 | | OTR | 188 | |
| 25 | 18.00 - 25 | | OTR | 236 | |
| 25 | 18.00 - 25 | | IND | 234 | |
| 25 | 18.00 R 25 | | OTR | 236 | |
| 25 | 18.00 - 25 DT | | OTR | 212 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------------|--------|-------|
| 25 | | 18.00 | R 25 DT | OTR | 212 |
| 25 | 61 | x 18.00 | - 25 | OTR | 226 |
| 25 | | 505 / 95 | R 25 | OTR | 232 |
| 25 | | 20 / 65 | - 25 | OTR | 196 |
| 25 | | 20.5 | - 25 | OTR | 228 |
| 25 | | 20.5 | R 25 | OTR | 228 |
| 25 | | 525 / 80 | R 25 | OTR | 228 |
| 25 | | 21.00 | - 25 | OTR | 292 |
| 25 | | 21.00 | R 25 | OTR | 292 |
| 25 | | 21.00 | - 25 DT | OTR | 282 |
| 25 | | 21.00 | R 25 DT | OTR | 282 |
| 25 | | 22 / 65 | R 25 | OTR | 224 |
| 25 | | 575 / 95 | R 25 | OTR | 286 |
| 25 | | 23.5 | - 25 | OTR | 282 |
| 25 | | 23.5 | R 25 | OTR | 282 |
| 25 | | 605 / 80 | R 25 | OTR | 286 |
| 25 | | 24.00 | - 25 | OTR | 358 |
| 25 | | 24.00 | R 25 | OTR | 358 |
| 25 | | 25 / 65 | - 25 | OTR | 276 |
| 25 | | 25 / 65 | R 25 | OTR | 276 |
| 25 | | 26.5 | - 25 | OTR | 344 |
| 25 | | 26.5 | R 25 | OTR | 344 |
| 25 | | 685 / 80 | R 25 | OTR | 348 |
| 25 | | 29.5 | - 25 | OTR | 410 |
| 25 | | 29.5 | R 25 | OTR | 410 |
| 25 | | 29.5 | - 25 DT | OTR | 402 |
| 25 | | 29.5 | R 25 DT | OTR | 402 |
| 25 | | 30 / 65 | - 25 | OTR | 368 |
| 25 | | 30 / 65 | R 25 | OTR | 368 |
| 25 | 67 | x 34.00 | - 25 NHS | AGR | 436 |
| 25 | | 35 / 65 | - 25 | OTR | 474 |
| 25 | 66 | x 43.00 | - 25 NHS | AGR | 524 |
| 25 | 66 | x 44.00 | - 25 NHS | AGR | 556 |
| | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|----------|------------|--------|-------|
| 26 | 14.9 | - 26 | AGR | 142 | |
| 26 | 14.9 | R 26 | AGR | 142 | |
| 26 | 16.00 | - 26 | OTR | 162 | |
| 26 | 16.9 | - 26 | AGR | 174 | |
| 26 | 16.9 | R 26 | AGR | 174 | |
| 26 | 18.00 | - 26 TG | OTR | 254 | |
| 26 | 18.4 | - 26 | AGR | 198 | |
| 26 | 18.4 | R 26 | AGR | 198 | |
| 26 | 480 / 70 | R 26 | AGR | 188 | |
| 26 | 23.1 | - 26 | AGR | 280 | |
| 26 | 28 L | - 26 | AGR | 344 | |
| 26 | 54 x 31.00 | - 26 NHS | AGR | 316 | |
| 26 | 67 x 34.00 | - 26 NHS | AGR | 436 | |
| 26 | 66 x 43.00 | - 26 NHS | AGR | 524 | |
| | | | | | |
| 28 | 11.2 | - 28 | AGR | 100 | |
| 28 | 11.25 | - 28 SL | AGR | 122 | |
| 28 | 12.4 | - 28 | AGR | 116 | |
| 28 | 320 / 70 | R 28 | AGR | 108 | |
| 28 | 13.6 | - 28 | AGR | 134 | |
| 28 | 13.6 | R 28 | AGR | 134 | |
| 28 | 360 / 70 | R 28 | AGR | 128 | |
| 28 | 14.9 | - 28 | AGR | 152 | |
| 28 | 14.9 | R 28 | AGR | 152 | |
| 28 | 380 / 70 | R 28 | AGR | 138 | |
| 28 | 420 / 70 | R 28 | AGR | 160 | |
| 28 | 16.9 | - 28 | AGR | 180 | |
| 28 | 16.9 | R 28 | AGR | 180 | |
| 28 | 18.4 | - 28 | AGR | 206 | |
| 28 | 480 / 70 | R 28 | AGR | 194 | |
| 28 | 19.6 | - 28 | AGR | 216 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|---------------------|------------|--------|-------|
| 29 | 20 / 65 - 29 | OTR | 210 | |
| 29 | 24.00 - 29 | OTR | 376 | |
| 29 | 24.00 R 29 | OTR | 376 | |
| 29 | 25 / 65 - 29 | OTR | 294 | |
| 29 | 26.5 - 29 | OTR | 364 | |
| 29 | 26.5 R 29 | OTR | 364 | |
| 29 | 29.5 - 29 | OTR | 438 | |
| 29 | 29.5 R 29 | OTR | 438 | |
| 29 | 30 / 65 - 29 | OTR | 392 | |
| 29 | 30 / 65 R 29 | OTR | 392 | |
| 29 | 33.25 - 29 | OTR | 516 | |
| 29 | 33.25 R 29 | OTR | 516 | |
| 29 | 35 / 65 - 29 | OTR | 500 | |
| | | | | |
| 30 | 14.9 - 30 | AGR | 158 | |
| 30 | 14.9 R 30 | AGR | 158 | |
| 30 | 420 / 70 R 30 | AGR | 166 | |
| 30 | 16.9 - 30 | AGR | 190 | |
| 30 | 16.9 R 30 | AGR | 186 | |
| 30 | 18.4 - 30 | AGR | 216 | |
| 30 | 480 / 70 R 30 | AGR | 202 | |
| 30 | 520 / 70 R 30 | AGR | 226 | |
| 30 | 23.1 - 30 | AGR | 292 | |
| 30 | 67 x 34.00 - 30 NHS | AGR | 436 | |
| | | | | |
| 32 | 24.5 - 32 | AGR | 334 | |
| 32 | 24.5 R 32 | AGR | 328 | |
| 32 | 30.5 L - 32 | AGR | 418 | |
| 32 | 30.5 L R 32 | AGR | 412 | |
| 32 | 30.5 L - 32 VA | AGR | 412 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | | | Tire Class | Ounces | Price |
|--------------|------------------|---------|---|----|------------|--------|-------|
| 32 | 33 | L | - | 32 | VA | AGR | 466 |
| 32 | 35.5 | L | - | 32 | VA | AGR | 522 |
| 32 | 35.5 | L | - | 32 | VA | AGR | 522 |
| 32 | 38 | L | - | 32 | VA | AGR | 582 |
| 32 | 40.5 | L | - | 32 | VA | AGR | 648 |
| 32 | DH 73 | x 44.00 | - | 32 | NHS | AGR | 614 |
| 32 | VA 73 | x 44.00 | - | 32 | NHS | AGR | 614 |
| 32 | 68 | x 50.00 | - | 32 | NHS | AGR | 650 |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|------------------|------------|--------|-------|
| 33 | 18.00 - 33 | OTR | 266 | |
| 33 | 18.00 R 33 | OTR | 266 | |
| 33 | 21.00 - 33 | OTR | 326 | |
| 33 | 27.00 - 33 | OTR | 500 | |
| 33 | 27.00 R 33 | OTR | 500 | |
| 33 | 30.00 - 33 | OTR | 562 | |
| 33 | 30 / 65 - 33 | OTR | 414 | |
| 33 | 33.5 - 33 | OTR | 558 | |
| 33 | 33.5 R 33 | OTR | 558 | |
| 33 | 35 / 65 - 33 | OTR | 526 | |
| 33 | 35 / 65 R 33 | OTR | 526 | |
| 33 | 37.5 - 33 | OTR | 664 | |
| 33 | 37.5 R 33 | OTR | 664 | |
| | | | | |
| 34 | 16.9 - 34 | AGR | 200 | |
| 34 | 18.4 - 34 | AGR | 230 | |
| 34 | 18.4 R 34 | AGR | 226 | |
| 34 | 480 / 70 R 34 | AGR | 216 | |
| 34 | 520 / 70 R 34 | AGR | 240 | |
| 34 | 20.8 - 34 | AGR | 268 | |
| 34 | 20.8 R 34 | AGR | 268 | |
| 34 | 23.1 - 34 | AGR | 310 | |
| 34 | 23.1 R 34 | AGR | 310 | |
| | | | | |
| 35 | 21.00 - 35 | OTR | 334 | |
| 35 | 21.00 R 35 | OTR | 334 | |
| 35 | 24.00 - 35 | OTR | 406 | |
| 35 | 24.00 R 35 | OTR | 406 | |
| 35 | 29.5 - 35 | OTR | 466 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|------|------------|--------|-------|
| 35 | 29.5 | R 35 | OTR | 466 | |
| 35 | 33.25 | - 35 | OTR | 566 | |
| 35 | 33.25 | R 35 | OTR | 566 | |
| 35 | 37.25 | - 35 | OTR | 660 | |
| 35 | 37.25 | R 35 | OTR | 660 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|---------|------------|--------|-------|
| 36 | 11.2 | - 36 | AGR | 114 | |
| 36 | 12.4 | - 36 | AGR | 136 | |
| 36 | 13.9 | - 36 | AGR | 154 | |
| | | | | | |
| 37 | 31.5 | - 37 | OTR | 198 | |
| 37 | 31.5 | R 37 | OTR | 198 | |
| | | | | | |
| 38 | 11.2 | - 38 | AGR | 122 | |
| 38 | 12.4 | - 38 | AGR | 140 | |
| 38 | 13.6 | - 38 | AGR | 158 | |
| 38 | 14.9 | - 38 | AGR | 176 | |
| 38 | 15.5 | - 38 | AGR | 182 | |
| 38 | 15.5 | R 38 | AGR | 182 | |
| 38 | 16.9 | - 38 | AGR | 212 | |
| 38 | 16.9 | R 38 | AGR | 212 | |
| 38 | 18.4 | - 38 | AGR | 240 | |
| 38 | 18.4 | R 38 | AGR | 240 | |
| 38 | 480 / 70 | R 38 | AGR | 230 | |
| 38 | 520 / 70 | R 38 | AGR | 256 | |
| 38 | 20.8 | - 38 | AGR | 284 | |
| 38 | 20.8 | R 38 | AGR | 284 | |
| 38 | 580 / 70 | R 38 | AGR | 300 | |
| 38 | 33 L | - 38 VA | AGR | 504 | |
| 38 | 35.5 L | - 38 VA | AGR | 562 | |
| 38 | 38 L | - 38 VA | AGR | 626 | |
| 38 | 40.5 L | - 38 VA | AGR | 694 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|------------------|------------|--------|-------|
| 39 | 33.5 - 39 | OTR | 596 | |
| 39 | 33.5 R 39 | OTR | 596 | |
| 39 | 37.5 - 39 | OTR | 706 | |
| 39 | 37.5 R 39 | OTR | 706 | |
| 39 | 40 / 65 - 39 | OTR | 698 | |
| 39 | 40 / 65 R 39 | OTR | 698 | |
| 39 | 40.5 / 75 R 39 | OTR | 774 | |
| 39 | 41.25 / 70 - 39 | OTR | 750 | |
| 39 | 45 / 65 - 39 | OTR | 842 | |
| | | | | |
| 42 | 18.4 - 42 | AGR | 254 | |
| 42 | 18.4 R 42 | AGR | 254 | |
| 42 | 20.8 - 42 | AGR | 300 | |
| 42 | 20.8 R 42 | AGR | 300 | |
| | | | | |
| 45 | 45 / 65 R 45 | OTR | 892 | |
| 45 | 50 / 65 - 45 | OTR | 1054 | |
| 45 | 55 / 65 - 45 | OTR | 1228 | |
| | | | | |
| 46 | 13.6 - 46 | AGR | 180 | |
| 46 | 13.6 R 46 | AGR | 180 | |
| 46 | 14.9 R 46 | AGR | 196 | |
| 46 | 18.4 R 46 | AGR | 268 | |
| 46 | 20.8 R 46 | AGR | 314 | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|-----------|------------|--------|-------|
| 49 | 18.00 | - 49 | OTR | 324 | |
| 49 | 18.00 | R 49 | OTR | 324 | |
| 49 | 21.00 | - 49 | OTR | 394 | |
| 49 | 21.00 | R 49 | OTR | 394 | |
| 49 | 24.00 | - 49 | OTR | 474 | |
| 49 | 24.00 | R 49 | OTR | 474 | |
| 49 | 27.00 | - 49 | OTR | 570 | |
| 49 | 27.00 | R 49 | OTR | 570 | |
| | | | | | |
| 51 | 24.00 | - 51 | OTR | 484 | |
| 51 | 27.00 | - 51 | OTR | 580 | |
| 51 | 30.00 | - 51 | OTR | 684 | |
| 51 | 30.00 | R 51 | OTR | 684 | |
| 51 | 33.00 | - 51 | OTR | 782 | |
| 51 | 33.00 | R 51 | OTR | 782 | |
| 51 | 36.00 | - 51 | OTR | 912 | |
| 51 | 36.00 | - 51 DT | OTR | 886 | |
| 51 | 36.00 | R 51 | OTR | 912 | |
| 51 | 36.00 | R 51 DT | OTR | 886 | |
| 51 | 37.5 | - 51 | OTR | 792 | |
| 51 | 37.5 | R 51 | OTR | 792 | |
| 51 | 50 | / 65 - 51 | OTR | 1110 | |
| 51 | 50 | / 65 R 51 | OTR | 1110 | |
| 51 | 55 | / 65 - 51 | OTR | 1290 | |
| 51 | 60 | / 65 - 51 | OTR | 1484 | |
| 51 | 65 | / 65 - 51 | OTR | 1690 | |
| | | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by Increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|----------------------|--|-------------------|----------------------|-------|
| 53 | 39 / 90 R 53 | OTR | 912 | |
| | | | | |
| 56.5 56.5 | 27 - 56.5 30 - 56.5 | OTR OTR | 480 570 | |
| | | | | |
| 57 57 57 | 37.00 R 57 40.00 - 57 40.00 R 57 | OTR OTR OTR | 1000 1128 1128 | |
| | | | | |
| 59.5 59.5 59.5 | 33 - 59.5 36 - 59.5 39 - 59.5 | OTR OTR OTR | 672 786 898 | |
| | | | | |

Arnco

ReSeal™ Volume Chart

(Listed by increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | Tire Class | Ounces | Price |
|--------------|-----------------------|------------|--------|-------|
| 6 | 18 x 7/4.50F | NHS IND | 24 | |
| 8 | 16 x 4.4 | AIR | 6 | |
| 8 | 18 x 5.5 | AIR | 8 | |
| 8 | 18 x 7 | IND | 26 | |
| 10 | 18 x 4.4 | AIR | 6 | |
| 10 | 24 x 7.7 | AIR | 12 | |
| 12.31 | 16 x 1.75 | CYB | 4 | |
| 12.31 | 16 x 2.125 | CYB | 6 | |
| 12.48 | 16 x 1 3/4 | CYB | 4 | |
| 13 | 21 x 4 | IND | 20 | |
| 13 | 22 x 4 1/2 | IND | 26 | |
| 13 | 23 x 5 | IND | 30 | |
| 13 | 25 x 6 | IND | 34 | |
| 14 | 26 x 6.6 | AIR | 12 | |
| 14 | 34 x 11 | AIR | 24 | |
| 14.31 | 18 x 1.625 | CYB | 4 | |
| 15 | 29 x 7.7 | AIR | 14 | |
| 16 | 32 x 8.8 | AIR | 18 | |
| 16 | 36 x 11 | AIR | 26 | |
| 16 | 39 x 13 | AIR | 32 | |
| 16 | 40 x 14 | AIR | 35 | |
| 16 | 42 x 15 | AIR | 42 | |
| 16.31 | 20 x 1.75 | CYB | 6 | |
| 16.31 | 20 x 1.75 / 47 - 406 | CYB | 6 | |
| 16.31 | 20 x 2.125 | CYB | 8 | |
| 16.48 | 20 x 1 3/4 | CYB | 6 | |
| 17.72 | CT 205 / 45 R 450 | PAS | 14 | |
| 17.75 | 20 x 1 1/4 | CYB | 4 | |
| 17.75 | 20 x 1.25 | CYB | 4 | |
| 17.75 | 20 x 1.375 | CYB | 4 | |
| 17.75 | 20 x 1 3/8 | CYB | 4 | |
| 18 | 40 x 12 | AIR | 32 | |
| 18 | 44 x 16 | AIR | 44 | |
| 20 | 46 x 16 | AIR | 46 | |
| 20 | 49 x 17 | AIR | 54 | |
| 20.30 | 24 x 2.125 | CYB | 8 | |
| 20.30 | 24 x 2.125 / 57 - 507 | CYB | 8 | |
| 20.31 | 24 x 1.75 | CYB | 6 | |
| 20.31 | 24 x 2.125 | CYB | 8 | |
| 20.48 | 24 x 1 3/4 | CYB | 6 | |

Arnco

ReSeal™ Volume Chart

(Listed by increasing Rim Diameter then by Tire Width)

| Rim Diameter | Tire Designation | | Tire Class | Ounces | Price |
|--------------|------------------|---------|------------|--------|-------|
| 21.24 | 24 | x 1 3/8 | CYB | 6 | |
| 21.52 | 24 | x 1 1/4 | CYB | 6 | |
| 21.75 | 24 | x 1.25 | CYB | 6 | |
| 21.75 | 24 | x 1.375 | CYB | 6 | |
| 22.31 | 26 | x 1.75 | CYB | 8 | |
| 22.31 | 26 | x 2.10 | CYB | 8 | |
| 22.31 | 26 | x 2.125 | CYB | 8 | |
| 22.48 | 26 | x 1 3/4 | CYB | 8 | |
| 23.24 | 26 | x 1 3/8 | CYB | 6 | |
| 23.51 | 26 | x 1 1/4 | CYB | 6 | |
| 23.75 | 26 | x 1.25 | CYB | 6 | |
| 23.75 | 26 | x 1.375 | CYB | 6 | |
| 24.49 | 700 | x 28 | C | 6 | |
| 24.79 | 27 | x 1 | CYB | 4 | |
| 24.79 | 27 | x 1 1/8 | CYB | 6 | |
| 24.79 | 27 | x 1 1/4 | CYB | 6 | |
| 24.79 | 27 | x 1 1/4 | HP | 6 | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |